

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1393)

Set ¼ sec. post, from which
A Fir 14" dia., bears S.38°W., 22 lks. dist.
A Cedar 6" dia., bears N.45°E., 35 lks. dist.

Survey by Wilford N. Haines - For: Jim Whipple - Aug. 15, 1975 Aug. 15, 1975

Found - 6" Cedar now 44".
Set 5/8" Steel rod, S.45°W., 35 lks. from BT.

Fd. OK, M 105-27

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Jan. 20, 1988 - C.S. File 62/50-6

Found - A 5/8" iron rod with "+" on top protruding 1" above ground.
6" now 47" dia. R.Cedar with a possible fully healed single blaze, bears N.45°E., 23.1 ft. (Orig. BT)
Orig. SW BT not found.
Orig. Elk Creek call checked and position agrees well with original record. (West, 80.5 ft.)
Set a 2 3/8" brass cap on a 1¼" outside dia. x 31" I.P. that protrudes 6" above ground. Cap mkd. "Douglas County Surveyors T22S ¼ S13 S24 R5W 1988". 5/8" I.R. referenced and BC/IP set in its place. 5/8" x 40" I.R. is set along North side of BC/IP protruding 4" above ground.
New BTs -17" Alder, bark scribed "¼ S24 CS BT", bears S.34°W., 26.0 ft.
11" Hardwood tree, double blazed and scribed "¼ S24 CS BT" bears S.46½°E., 5.9 ft.
13" Ash, double blazed and scribed "¼ S24 CS BT", bears S.82¼°E., 24.0 ft.
Cor. lies near an E-W fence line and Elk Creek on East side of creek.

Fd. OK, Feb. 1999 by D.Baker - M129-46

DCSO-GIS Corner visitation - 10/20/2005 - Typed: 1/19/2011 - C.S. File 67/33-1

Monument - 1¼" ip w/BC.
Comment - OK; 3 live BTs, 1 snag.