

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 4 Page(s) 1420)

Set post 4" dia., 4 ft. long with mkd. stone 12" in ground for 1/4 sec. cor. mkd. 1/4 S on N face; from which

A Laurel 8" dia., bears N.70°E., 14 lks. dist. mkd. 1/4 S BT

A Laurel 8" dia., bears S.57°E., 23 lks. dist. mkd. 1/4 S BT

Survey by B.H. McGillicuddy - For: Whipple Lumber Co. - April 1952 - RM 1-40

Orig. bearing trees destroyed.

Cor. established by single proportion between sec. corners. Scribed BTs

22" Fir S.62°E., 43.8 ft. mkd. S 1/4 R.P. BT.

34" Fir N.33°W., 81.5 ft. mkd. S 1/4 R.P. BT.

Searched for, not found, DCSO, May 1965, C.S. File 53/101-14

Orig. cor. searched for, not found. Aug. 1972, B. Shaner, - M 42-68 (Cor. set by McGillicuddy found but not usable as he had improperly set the SW corner Sec. 1)

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1103, surveyed July 1982 (DCSO records Vol. 46 Page(s) 17593-94)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an alum. post, 28" long, 2 1/2" dia., 24" in the ground, with alum. cap mkd:

T	22	S	R	5	W
		S	1		
1/4		S	12		
					1982

from which

A Fir 16" dia. bears N.30 1/2°E., 33 1/2 lks. mkd. 1/4 S1 BT.

A Fir 11" dia., bears S.5°E., 35 lks. dist. mkd. 1/4 S12 BT

From this point, a cor. established by McGillicuddy in 1952, bears N.58°04'E., 0.50 chs. dist., monumented with a mound of stone, 2 ft. base, 1 ft. high, from which BTs mkd. by McGillicuddy

A sawed Fir stump 22" dia., bears S.56 1/2°E., 68 lks. dist. with axe marks visible on an opened blaze.

A Fir 45" dia., bears N.33°W., 123 lks. dist. with a healed blaze.

Fd. ok Dan Baker, 6/1999 - M 132-5 continued next pg

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias	Description

DCSO-GIS Corner visitation - 9/28/2005 - Typed: 1/19/2011 - C.S. File 67/33-1

Monument - 3" AC on 2½" AP. Comment - (needs rehab)

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - Jason Martin - July 21, 2011 - C.S. File 67/33-42

Found - (1982) A 3⅞" dia., alum. cap (properly mkd) on a 2½" O.D. iron pipe is firmly set & protrudes 6" above ground. Stamping on cap is oriented South. Some loose stones are found near rec. bearing & dist. noted in 1982 resurvey for McGillicuddy corner. Monument (stones too few and scattered for any reasonable measurement)

Search made for 1884 Laurel OBTs, no evidence found. From the above noted McGillicuddy scattered stone, evidence of the 2 1952 BTs is found at position that agrees reasonably with the 1952 rec. The SW 22" Fir is now a mostly rotted away fir tree stump and the NW 34" fir is now a 45" dia., 3 ft. tall rotted fir stump with a possible healed blaze (not opened)

(1982 (BLM cap)) A fir 16" dia., now a 2 ft. tall 21" dia., fir stump with a partially healed single blaze (mostly rotted away) showing some illegible scribing and a "BT"; bears N.30½°E., 22.1 ft. (as per rec.)

(1982 (BLM cap)) A fir 11" dia., now a 17" DBH D.Fir with a fully healed single blaze bears S.7¾°E., 22.6 ft. (rec. S.5°E., 23.1 ft. base is some what pistol-butt, may account for discrepancy)

New BTs- A 7" DBH D.Fir scribed "¼ S1 CS" "BT" on a double blaze; bears N.9½°E., 3.7 ft.

A 12" DBH G.Fir scribed "¼ S12 CS" "BT" on a double blaze; bears S.47½°E., 24.4 ft.

A 9" DBH D.Fir scribed "¼ S12 CS" "BT" on a double blaze; bears S.54°W., 14.9 ft.

Note - Monument is on a moderate WSW slope at the north edge of a newer clear-cut and the south edge of an older fir reprod. forest.

Compass decl. 15¾°E.