

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T22-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1333)

Set post, cor. of secs. 25, 30, 31 and 36, from which
A Fir 36" dia., bears N.52°W., 41 lks. dist.
A Fir 40" dia., bears N.37½°E., 87 lks. dist.
A Fir 24" dia., bears S.37°E., 33 lks. dist.
A Fir 30" dia., bears S.16°W., 46 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew,
S.A. Bilow - April 22, 1959 - C.S. File 49/59-31

Found - Orig. 36" now 44" Fir, N.52°W., 27.1 ft., shows good bark scribe near base "BT"
Orig. 30" now 40" Fir stump, S.16°W., 30.4 ft. I open and find good scribe "6"
Orig. 24" now 30" stump, shows good scar, I do not open, S.37°E., 26.0 ft., record S.37°E., 21.8 ft.
No trace of orig. NE BT.

Set Brass cap at cor. mkd: County Surveyors Office
T22S
R5W

S25	S30
S36	S31

 R4W
1959

New BTs -62" R.Fir bears N.15°E., 130.0 ft. scribed S30 T22S
R4W CS BT.
12" Cedar bears S.13½°E., 92.0 ft. scribed S31 T22S
R4W CS BT.
6" R.Fir bears S.78°W., 39.2 ft. scribed S36 CS BT.

Fd. OK, Dec. 1983, L.Smith, M 95-74

BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, under Group # 812 Surveyed Aug./Sept. 1973 (DCSO records Vol. 36 Page(s) 15058)

The Sec. cor., perpetuated by Byron in 1959, monumented with an iron post, 2¼" dia., firmly set, protruding 8" above ground with 1959 brass cap.

from which the remains of the original bearing trees
A sawed Fir stump 30" dia., bears S.37°E., 39½ lks. dist., with healed blaze. (Rec. 33 lks.)
A sawed Fir stump 40" dia., bears S.16°W., 46 lks. dist., with scribe mark 6 visible on opened blaze.
A root hole bears N.52°W., 41 lks. dist., with a down Fir alongside 44" dia., no marks visible.

and bearing trees mkd. by Byron
(Cont. Next Page)

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. 25 & 36; 30 & 31, T22-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 63" dia., bears N.15°E., 197 lks. dist., with healed blaze.
A Cedar 25" dia., bears S.13½°E., 139 lks. dist., with healed blaze.
A Fir 13" dia., bears S.78°W., 59½ lks. dist., with healed blaze.
and a new bearing tree
A Fir 6" dia., bears N.41°W., 56½ lks. dist., mkd. T22S R5W S25 BT.
Corner is located at the intersection of wire fences extending N., E., and W.

Fd. OK, Mar. 1997 by K. Hoffine - M 124-47