

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 038010

PRIMARY CORNER DESCRIPTION NE Cor. Jos. Putnam DLC #38

Alias <u>039020</u>	Description <u>NW Cor. Chas. Putnam DLC #39</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,  
dated Sept. 1856

-----  
Set post, from which  
    An Alder 24" dia., bears S.70°E., 420 lks.  
    An Alder 18" dia., bears S.87°E., 410 lks.

Survey by George Scroggin - For: Plat of Sunnydale Orchards  
-Aug. 6, 1914 - Plat Vol. 5 Page 20 A&E

-----  
The Initial Point of said survey, said monument is at the  
northwest corner of the C. Putnam DLC, said monument being a  
galv. iron pipe 2" in dia. 3 ft. long driven 6" below the  
surface of the ground.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 6/19/2001 - C.S. File 66/21-27

-----  
Found - ½" I.D. driven iron pipe 8" below ground. (Rec. 2"  
IP, Sub. Vol. 5 Pg. 20A) No BTs found. IP  
measures 34" long.

Tie between this IP and possible position of the NW  
cor. DLC 38, bears S.89°43'W., 2227.8 ft. (staff  
compass decl. 17½°E.) (Rec. N.89°46'W., 2223.5  
ft., Sub. Vol. 5 Pg. 20A)

Tie between this IP & probable position of the SW  
cor. DLC 38 as determined by found IP bears  
S.0¼°W., 5307.0 ft. (staff compass decl. 17½°E.)  
(rec. South 5299.8 ft. orig. DLC survey)

To protect found position of I.P.:  
Set - We set I.P. at position found, 8" below ground. A  
5/8" x 30" long iron rod is set alongside, plumb  
over top, with a DCS0 plastic cap, protrudes 5"  
above ground.

References -  
    SE concrete corner, stem wall of feeder shed, bears  
    N.11¼°E., 199.2 ft.  
    SW concrete corner, stem wall of feeder shed, bears  
    N.9¼°W., 170.2 ft.  
    12" dia., Pear double blazed & scribed "X CS BT"  
    bears S.37°E., 280.8 ft.

Found OK by W. Eimstad, June 2002 - M140-58  
Fd. 5/8" IR per rec. 9/2024 by M Helm - M184-28