

PRIMARY CORNER DESCRIPTION NW Cor. Jos. Putnam DLC #38

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy, dated Sept. 1856  
-----  
Set stone post 6 x 8 x 18" in NW cor. Cl. 38, from which  
    An Oak 18" dia., bears N.30°W., 211 lks.  
    An Oak 18" dia., bears N.4° (or 40°)W., 254 lks.

Survey by George Scroggin for: Plat of Sunnydale Orchards - Aug. 6, 1914 - Plat Vol. 5 Page 20 A&B  
-----  
Stone

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 6/18/2001 - C.S. File 66/21-26 A&B  
-----  
Found - Stone loose on top of ground, no position. Measures 6"x8"x16" no marks (rec. 6"x8"x18") **Orig.?**  
    3/4" dia., x 13" long shaft with a smashed top loose on top of ground, no position (rec. Rod) rec. S.0°22'E., 12.79' from stone, Sub. Vol. 5 Pg. 20A  
    Remains of Two old Oaks that bears N.51°E., 71.3 ft. between them. They would agree well with a rec. of N.30°W., 139.3 ft. to a rotted stump no marks found and N.4°W., 167.6 ft. to a 28" dia., Oak snag that has old fence wire grown into it. We open & find old axe marks, no scribing found. Records show this BT as N.40°W. or N.4°W.  
    **From position determined from possible Orig. BTs,**  
    N.30°W., 139.3' and N.4°W., 167.6'  
    Stone bears N.80°E., 16 ft.  
    Shaft bears N.50°W. 22 ft.  
    Area around corner shows evidence of bulldozer scars & field work from years past.  
    A search was made for the NW corner of DLC 39, Fd. 1/2" I.D. driven iron pipe 8" below ground no BTs found. (Rec. 2" IP, Sub. Vol. 5 Pg. 20A) tie between corners made, bears N.89°43'E., 2227.8 ft. (staff compass decl. 17 1/2°E.) (Rec. S.89°46'E., 2223.5 ft., Sub. Vol. 5 Pg. 20A)  
    **To protect evidence as found:**  
Set - A 5/8"x30" long iron rod with DCSO plastic cap is set at position as determined by possible OBTs N.30°W., 139.3' and N.4°W., 167.6 ft. protrudes 1" above ground.  
    Found stone is placed along easterly edge of I.R.  
    Found shaft is set along southerly edge of I.R., flush w/ground. continued next page

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 038020

PRIMARY CORNER DESCRIPTION NW Cor. Jos. Putnam DLC #38

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New References -

30" dia., W.Oak double blazed & scribed "X CS BT"  
bears N.72°W., 67.9 ft.

21" dia., D.Fir double blazed & scribed "X CS BT"  
bears N.0 3/4°W., 91.0 ft.

Compass decl. 17½°E.