

PRIMARY CORNER DESCRIPTION Int. SW Cor. Jos. Putnam DLC #38

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>Surveys of Donation Land Claims by - Dennis Hathorn, Deputy, dated Sept. 1856</p> <p>-----</p> <p>Marked an Oak 6" dia., interior corner Claim 38, from which A Fir 24" dia., bears S.1°E., 25 lks. An Oak 6" dia., bears N.42°E., 36 lks.</p>	
<p>Survey by George Scroggin for Plat of Sunnydale Orchards, Aug. 6, 1914 - Plat Vol. 5 Page 20 A&B</p> <p>-----</p> <p>Bolt</p>	
<p>Wilford N. Haines - For: H.A. Cool - Sept. 10, 1970 - M 40-35</p> <p>-----</p> <p>Found 1¼" Iron pipe in place for DLC corner.</p>	
<p>Fd. OK by M. Heimbürger, Nov. 2000 - M136-10</p>	
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 6/21/2001 - C.S. File 66/21-29</p> <p>-----</p> <p>Found - Iron bolt with 1" square head driven into base of a 11" dia., 4 ft. high rotted Oak snag. Orig. corner tree? Bolt from 1914. Note: tree has rotted down in size has a base of approx. 25" in dia.</p> <p>24" now 30" dia., 7 ft. high pistol butt, rotted D.Fir snag scribing. Fd. part of a "B" and "T" bears S.5°W., 19.5 ft. to center 18.3 ft. to face (rec. S.1°E., 16.5 ft.) OBT</p> <p>NE BT not found.</p> <p>Probable location of M10-51 fd. IP now at concreted fence post N.43°W., 7.1 ft.</p> <p>New - 21" dia., W.Oak double blazed & scribed "INT L DLC 38 CS BT" bears N.88°W., 86.4 ft.</p> <p>12" dia., D.Fir double blazed & scribed "INT L DLC 38 CS BT" bears N.48°E., 41.6 ft.</p> <p>13" dia., W.Oak double blazed & scribed "INT L DLC 38 CS BT" bears S.42°W., 26.3 ft.</p> <p>9" dia., B.Oak growing out of old root wad, single blazed & scribed "INT L DLC CS BT" bears S.8°E., 2.0 ft.</p> <p>Compass decl. 17½°E.</p>	
<p>1</p>	