

PRIMARY CORNER DESCRIPTION SW Cor. of Chas. Putnam DLC #39

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>Surveys of Donation Land Claims by - Dennis Hathorn, Deputy, dated Sept. 1856</p> <p>-----</p> <p>Set post, from which</p> <ul style="list-style-type: none"><li>A Fir 15" dia., bears S.5°E., 30 lks.</li><li>An Ash 5" dia., bears N.30°E., 10 lks.</li><li>A Fir 30" dia., bears S.5°W., 30 lks.</li></ul>
<p>Ben B. Irving, Deputy Co. Surveyor - Wit: W.S. Crear; Geo. Montgomery - Jan. 1928 - C.S. File 22/25</p> <p>-----</p> <p>Set 1½" x 30" Iron pipe driven flush with ground from original BTs. Remarked original BTs.</p> <ul style="list-style-type: none"><li>36" Fir S.5°E., 30 lks. dist.</li><li>40" Fir S.5°W., 30 lks. dist.</li></ul>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 6/20/2001 - C.S. File 66/21-28</p> <p>-----</p> <p>Found - 1½" I.P. 30" below ground. (1928?) No BTs found.</p> <p>Set - 5/8"x60" long iron rod in center of found iron pipe, protrudes 1" above ground with DCSO plastic cap. Fd. iron pipe was driven 48" under ground, (Note: area subject to flooding we feel the long monument gives the best protection)</p> <p>Found ½" I.P. possible NW cor. DLC 39 bears N.0¼°E., 5307.0 ft. (staff compass decl. 17½°E.) (Rec. North, 5299.8 ft. Orig. DLC survey)</p> <p>22" dia., Ash double blazed &amp; scribed "X CS BT" bears S.72½°E., 19.6 ft.</p> <p>1961 DCSO brass cap iron pipe WC ¼ S16 S15 bears S.79½°E., 577.2 ft.</p> <p>Center of North concrete bridge pier bears N.85°E., approx. 610 ft.</p> <p>21" dia., W.Oak double blazed &amp; scribed "X CS BT" bears S.80¼°E., 155.6 ft.</p>
<p>Found OK by W. Eimstad, June 2002 - M140-58</p>
<p>1</p>