

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>Surveys of Donation Land Claims by - Dennis Hathorn, Deputy, dated Sept. 1856</p> <p>-----</p> <p>A Fir 5" dia., from which A Dogwood 6" dia., bears N.20°W., 18 lks. A Fir 30" dia., bears S.10°E., 31 lks.</p>
<p>Ben B. Irving, Deputy Co. Surveyor - Wit: W.S. Crear; Geo. Montgomery - Jan. 1928 - C.S. File 22/25</p> <p>-----</p> <p>Position determined by intersection of E. and S. lines of the claim. Set Boulder 7" x 10" x 10" flush with the ground. A 20" Fir S.19°E., 89.8 lks. dist. scribed Cl. 39 CS BT. A 20" Fir N.19°W., 68.9 lks. dist. scribed Cl. 39 CS BT.</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 12/19/2001 - C.S. File 66/29-29</p> <p>-----</p> <p>Found - 1928 stone not found. 20" now broken rotted D.Fir stump, scribing "BT" fd. bears S.19°E., 59.3 ft. No other BTs found. 5/8"x60" long iron rod with alum. cap is set at record brg &amp; distance from 1928 SE BT. Alum DCSO cap on top marked "SE 39 2001". Protrudes 5" out of ground.</p> <p>Note that corner lies on steep North slope.</p> <p>New - 36" dia., 5 ft. high D.Fir stump set 8" boat spike through BT tag at top center bears S.45°W., 12.1 ft. (B.S. stamped B02) 17" dia., 1½ ft. high D.Fir stump set 8" nail through BT tag near top center bears N.8°W., 7.6 ft. (nail stamped B03) 36" dia., 3 ft. high D.Fir stump set 8" boat spike through BT tag near top center, bears N.51½°E., 34.6 ft. (B.S. stamped B01)</p>
<p>1</p>