

PRIMARY CORNER DESCRIPTION SW Cor. Swearinger DLC #42

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,
dated Sept. 1856

Set Post, from which
 An Oak 24" dia., bears S.5°E., 346 lks.
 An Alder 15" dia., bears S.58°E., 212 lks.

Wilford N. Haines - For: Harold Woolley - Dec. 1957 - M 8-30

Found - Oak BT, snag, to South for SW corner.
 DLC #42 corner bears S.84°37'E., 1199.54 ft. from SW
 cor. Sec. 35, T21-6.
 Scribed -12" W.Oak S.87°15'W., 23.2 ft.
 22" W.Oak N.89°30'E., 40.5 ft.
 Set 1" x 1" x 36" Iron Rod with brass cap.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
 Stephen J. Flause - 8/9/2001 - C.S. File 66/21-32

Found - Haines "T" iron bent protrudes 14" above ground 1957
 corner is North 4 ft. of an E-W fence line.
 12" now 26" dia., W.Oak with a fully healed single
 blaze bears S.87¼°W., 23.2 ft. (1957)
 22" now 37" dia., W.Oak with a fully healed double
 blaze bears N.89½°E., 40.5 ft. (1957)
 Orig. BTs not looked for.

Set - A 2 3/8" dia., brass cap on a 1 3/8" by 32" long
 iron pipe at plumb position of found "T" iron,
 protrudes 7" above ground. "T" set along East
 edge of BC/IP protrudes 12" out of ground. Marked

DOUGLAS COUNTY SURVEYORS
 T22S
 R | DLC
 6 | 42
 W | _____
 2001

10" dia., W.Oak double blazed & scribed "SW DLC 42
 CS BT" bears S.30½°E., 56.0 ft.
 Compass decl. 17½°E.