

PRIMARY CORNER DESCRIPTION NE Cor. Ensley DLC #44

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>Surveys of Donation Land Claims by - Dennis Hathorn, Deputy, dated Sept. 1856</p> <p>-----</p> <p>Set post, from which</p> <ul style="list-style-type: none"><li>An Oak 24" dia., bears N.10°W., 725 lks.</li><li>An Oak 12" dia., bears N.12°W., 761 lks.</li></ul>
<p>F.C. Frear, Deputy Co. Surveyor - Wit: J.W. Harness; Earl Frier - Dec. 1917 - C.S. File 1/4; Vol. 3 Page 3 and M 1-6</p> <p>-----</p> <p>Renew from old BTs.</p> <p>Set in or buried an 8" x 10" x 14" sandstone, from which</p> <ul style="list-style-type: none"><li>A 24" Oak bears N.10°W., 7.25 chs. dist.</li><li>A 12" Oak bears N.12°W., 7.61 chs. dist.</li><li>An 8" Apple bears S.61°W., 3.26 chs. dist.</li></ul>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 9/5/2001 - C.S. File 66/29-3</p> <p>-----</p> <p>Found - (M1-6) 1917 stone exposed top measured 5"x8" w/large chiseled "+" on top. Stone found 6" below ground. Haines T iron found along South edge 4" below ground probably set by Haines in 1954 (M4-19) 24" now 26" dia., rotted shell of Oak in large root hole, bears N.10°W., 478.5 ft. (OBT)</p> <p>No other BTs found.</p> <p>Stone top measures 9"x5" protrudes 2" out of ground with bent ½" dia., by 36" long bolt along north edge of stone we straighten and set in hole on North edge of stone 2" below ground. Bolt bears West 358.1 ft. (M1-6) 1917</p> <p>Haines "T" iron at E-W and S fence corner protrudes 12" out of ground, bears S.85¼°W., 260.9 ft. (M29-52) 1965</p> <p>New - 10" dia., W.Oak double blazed &amp; scribed "NE DLC 44 CS BT" bears S.32°W., 253.0 ft.</p> <p>23" dia., Ash double blazed &amp; scribed "NE DLC 44 CS BT" bears S.17¾°W., 250.0 ft.</p> <p>10" dia., Willow single blazed low "X BT" bears N.1¾°W., 139.2 ft.</p> <p>E-W &amp; N fence corner bears S.42°W., 25.6 ft.</p> <p>Metal wit. post &amp; sign in E-W fence line bears South 18.5 ft.</p> <p>Compass decl. 17½°E.</p>
<p style="text-align: right;">1</p>