

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 31 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Special Instructions dated Oct. 27, 1897 (DCSO records Vol. 4 Page(s) 1463)

Set a Maple post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., mkd. ¼ S on W. face; from which
 A Fir 16" dia., bears N.52°E., 20 lks. dist. mkd. ¼ S BT.
 A Fir 14" dia., bears N.70°W., 81 lks. dist. mkd. ¼ S BT.
(From this cor., the old ¼ sec. cor. bears S.16°42'E., 261 lks. dist. I destroy old cor.) (Old cor. in Vol. 4 Pg. 1431)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy; Clete Putnam, crew - Aug. 1961 - C.S. File 49/143-64

Found - Haines T Iron and cap at corner. (Record source not found)
 Fir tree, now 30", has been opened previously and good scribing "T" found.
 No trace of NW BT.
New BT - 23" D.Fir N.21°E., 27.6 ft. mkd. ¼ S31 CS BT.
Did Not Set Brass Cap.

Fd. OK, Feb. 1994, K. Hoffine, C.S. File 63/154-5
FD. Ok by K.Hoffine, Feb. 1995 - C.S. File 63/161-27