

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. cor. for 19 and 30 only (W. bdy)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Carl S. Nicklin, Deputy Surveyor, under Special Instructions dated Oct. 27, 1897 (DCSO records Vol. 4 Page(s) 1461)

Set a sandstone 12x10x8 ins., 8" in the ground, for cor. of secs. 19 and 30, mkd. with 4 notches on N. and 2 on S. edges; from which

A Fir 36" dia., bears N.80°E., 91 lks. dist. mkd. T22S R6W S19 BT.

A Maple 12" dia., bears S.20°E., 21 lks. dist. mkd. T22S R6W S30 BT.

This cor. is near the top of spur.

Wilford N. Haines - For: Whipple Mill - 1955 - M 2-13

Found old Fir BT.

Set angle iron with brass cap inscribed, Survey Point-Wilford N. Haines 239.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & C. Putnam, crew - Sept. 1961 - C.S. File 49/143-65

Found - Fir tree, now 42", N.80°E., 13.9 ft. (21 lks. instead of 91 lks.) Old scribing "S6W S19B" found.

Maple stool, showing evidence of a shoot, North of present shoots, broken off and rotted away, bears S.20°E., 91 lks. instead of 21 lks. (Scribing found of Maple, Nov. 1961 C.S. 49/143-2)

I believe distances to these BTs were reversed in Nicklin's notes. The C.C. of Secs. 24 & 25, T22-7, bears South from this cor. 281.8 ft., record was South 266.6 ft. Also calls on creek crossings and top of spur North and South of this point fit orig. calls.

Set Brass cap at cor. mkd: County Surveyors Office

T 22 S R 6 W

| S 19

| S 30

1961

New BTs -7" Fir S.57°E., 9.6 ft. mkd. S30 CS BT.

5" Fir N.36°E., 11.6 ft. mkd. S19 CS BT.

From this corner, Haines monument for same corner, bears S.75°W., 48.0 ft.

Survey by Ken Hoffine - For: Lone Rock Timber Co. - July 1990
C.S. File 63/129-1

(Cont. Next Page)

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec cor for 19 & 30 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Found - 1961 County brass cap 0.7 ft. above ground in good condition.
9" D.Fir bears S.57°E., 9.6 ft. well healed face and BT tag.
48" D.Fir bears N.80°E., 13.5 ft. (old bark scribe and chopped out face) and 4 alum. tags.
8" D.Fir bears N.30°E., (rec. N.36°E.) 11.6 ft. well healed face and BT tag.
New BT - Put Lone Rock Timber location tag on a 12" D.Fir bearing S.77°E., 2.4 ft. Tree is heavily blazed. Painted faces and wrote BT on tree trunks with fluorescent orange paint. Corner lies on South edge of spur ridge sloping NE. Very steep East side slope approx. 260 ft. West of creek.

Fd. OK, Feb. 1994, K. Hoffine, C.S. File 63/154-5

Ken Hoffine - Jun. 1995 - C.S. 65/1-5

Mon. Fd. - County Brass cap
BT's Fd. - 48" D.Fir, bears N.80°E., 13.5', chopped out face and 4 tags.
9" D.Fir, bears S.57°E., 9.6', well healed face and BT tag.
8" D.Fir, bears N.30°E., 11.6', (rec. N.36°E.) well healed face and BT tag.
12" D.Fir, bears S.77°E., 2.4', LRT location tag.
Haines T-Bar .4' above ground, bears S.74°37"E., 47.9'.
corner sits on south edge of spur ridge sloping N.E. with very steep east side slope. Approximately 260' west of creek.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2653, Surveyed June/July 2012 - DCS0 records Vol. 58 Page(s) 22993

The cor. of secs. 19 and 30 only, on the W. bdy. of the Tp., perpetuated by Haines, in 1955, further perpetuated by Godfrey, in 1961, monumented with an iron post, 1¼" dia., firmly set, projecting 13" above ground, with brass cap (properly) mkd.
from which the remaining original bearing tree
A fir, 46" dia., bears N.80°E., 13.9 ft., with no marks visible on an opened blaze. (Record, 60.1 ft.)
and an accessory mkd. by Haines
A "T" shaped iron rod, ¾" dia., firmly set, projecting 11" above ground, for a reference monument, bears S.74°18'13"W., 47.73 ft., with brass disk on top, mkd.
WILFORD N HAINES 239 SURVEY POINT DRAIN ORE (cont)

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. cor. for 19 and 30 only (W. bdy)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and bearing trees mkd. by Godfrey

A fir, 10" dia., bears N.36°E., 11.3 ft., with a healed double blaze.

A fir, 9" dia., bears S.53°E., 9.7 ft., with a healed blaze.

(Note: Godfrey recovered the remains of the original maple bearing tree with scribing visible at S.20°E., 91 lks., and determined the distances to the original bearing trees were reversed in Nicklin's notes.)

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2875, surveyed Aug. 2017/Feb. 2019 - (DCSO records Vol. 59 Page 23639-23640)

The cor. of secs. 19 & 30 only, on the W. bdy. of the Tp., monumented with an iron post, 1¼" dia., firmly set, projecting 11" above ground, with a brass cap (properly) mkd. from which the remaining original bearing tree

A fir, 52" dia., bears N.80°E., 13.9 ft., with no marks visible on open blaze.

and an accessory mkd. by Haines, in 1955

A "T" shaped iron rod, ¾" dia., firmly set, projecting 11" above ground, bears S.74°18'13"W., 47.73 ft., with a brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center.

and the BTs mkd. by Godfrey, in 1961, filed as CS 49/143-65

A fir, 11" dia., bears N.36°E., 11.3 ft., with a healed double blaze.

A fir, 9" dia., bears S.53°E., 9.7 ft., with a healed double blaze.