

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 19 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Special Instructions dated Oct. 27, 1897 (DCSO records Vol. 4 Page(s) 1460-61)

-----  
Set a Dogwood post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor. mkd. ¼ S on W. face; from which  
A Fir 30" dia., bears N.58°E., 73 lks. dist. mkd. ¼ S BT.  
A Fir 48" dia., bears S.30°W., 19 lks. dist. mkd. ¼ S BT.  
This cor. is on the S. slope of ridge, about 300 ft. below top. I could find no trace of the old ¼ sec. cor.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - Aug. 1961 - C.S. File 49/143-63

-----  
Found - Haines T Iron and cap. (No record)  
Fir tree, now 54", S.30°W., 12.5 ft. Has been opened previously and face burned out but portions of unmistakable scribing visible. This tree has been rescribed in bark ¼ S 363 BT.  
Portions of Fir stump N.58°E., 48.2 ft. found. No marks found.  
Blaze and scribe one new tree:  
12" D.Fir N.22°E., 46.1 ft. mkd. ¼ S19 CS BT.

Ken Hoffine - Jun. 1995 - C.S. 65/1-5

-----  
Mon. Fd. - Haines T-iron .4' below ground  
Bt's Fd. - 6" D.Fir, bears S.49½°E., 10', visible scribing with LRT Tag  
43" D.Fir stump (OR. B.T.) with tin cap, bears S.87¼°W., 12.9', face is burned out.  
26" D.Fir, bears N.54½°W., 3.4', a well healed face with spike at bottom.  
Decayed rootwad, bears S.73°E., 45.2'  
corner lies on a bench gently sloping to the south approximately 540' north of Thistleburn road.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2875, surveyed Aug. 2017/Feb. 2019 - (DCSO records Vol. 59 Page 23640)

-----  
The ¼ sec. cor. of sec. 19 only, on the W. bdy. of the Tp., perpetuated by Haines, date unknown, further perpetuated by Godfrey, in 1961, monumented with a "T" shaped iron rod, ¾" dia., firmly set, projecting 3" above ground, with brass washer mkd. WILFORD N. HAINES SURVEY POINT 239 DRAIN, ORE., with a tack in center, from which the remains of an original bearing tree  
Continued next page

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 100340

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 19 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A tin-capped, sawed, decayed fir stump, 48" dia., bears S.30°W., 12.5 ft., with no marks visible on open burnt blaze.

and the remains of a bearing tree mkd. by Godfrey, in 1961

A roothole bears N.24½°E., 44.5 ft., alongside of which is a down decayed fir, 12" dia., no marks visible.

and a bearing tree mkd. by person(s) unknown, recorded by Hoffine PLS No. 2281, in 1995

A fir, 9" dia., bears N.83¾°E., 9.6 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the iron rod, 32" long, with brass cap (properly) mkd.

T 22 S  
R7W | R6W  
      | ¼  
      | S19  
      2017

from which

A fir, 10" dia., bears S.55¼°E., 52.8 ft., mkd. ¼ S19 BT. Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.