

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; & 13, T22-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1432)

-----  
Set ¼ sec. post, from which  
A Fir 12" dia., bears N.85°W., 27 lks. dist.  
A Maple 10" dia., bears S.55°E., 10 lks. dist.

-----  
Wilford N. Haines - For: Chester Swerigen and Harold Woolley  
1956 - M 3-22 (and H-102)

-----  
Found - Orig. Fir BT.  
Maple is dead and down.  
Set an angle iron with brass cap inscribed Survey Point-  
Wilford N. Haines #239  
(Wording from H-102: 12" Fir N.08°30'E., 26.3 ft.  
Rescribed (bark) original BT to West, 51" Fir.)

-----  
Fd. OK, March 1994, K. Hoffine, M 119-23

-----  
Ken Hoffine - for Lone Rock Timber Co. - Dec. 1994 - M 121 -  
43

-----  
Found - Haines T-iron  
24" D.Fir, bears N.8°E. 24.5 ft., no face, 3 B.T.  
tags  
52" D.Fir, bears S.10°W. 25 ft., no face, LRT  
location tag.  
Orig. 12" D.Fir, is a 55" rotten stump, bears  
N.85°W. 17.8 ft., old face visible, no scribing.  
Orig. 10" Maple, is a 21" wind fall, bears S.55°E.  
6.6 ft., no visible scribing.  
Corner lies on a 50% southwest slope. BLM clearcut to the  
Northwest.

-----  
Douglas Co. Surveyors Office - Randall Smith, Deputy - Jan.  
20, 1995 - C.S. file 64/58-3

-----  
Found - Haines T-Iron with 1" dia. washer on top mkd.  
"Wilford N. Haines 239-Survey Point Drain Ore",  
protrudes 10" above ground.  
12" now 55" dia. 4 ft. high rotted D.Fir stump bears  
N.85°W., 17.8 ft. (agrees w/rec) O.B.T. We open  
and find scribing "BT"  
10" now 21" dia. down and rotted Maple, bears  
S.55°E., 6.6 ft. (agrees w/rec) O.B.T. We open,  
no scribing found.

(Cont. Next Page)

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; & 13, T22-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

24" dia. D.Fir, no blazes, bears N.8°E., 23.7ft.  
(Rec. N.8°E., 24.5 ft.) We double blaze and  
scribe "¼ S13 CS BT"  
52" dia. D.Fir, no blazes, bears S.10°W., 25.0 ft.  
(agrees w/rec.) We bark scribed "¼ S18 CS BT"  
Haines T-Iron is referenced and removed. At referenced  
position, a 2½" dia. DCSO brass cap on a 1 3/8" x 32" long  
iron pipe is SET. BC/IP protrudes 9" above ground. 24" long  
Haines T-Iron is set along South edge of BC/IP, protrudes 4"  
above ground. BC is mkd: Douglas County Surveyors  
T 22 S  
R R  
7 S13|S18 6  
W 1/4 W  
1995  
Office  
New BTs -12" dia. Maple double blazed and scribed "¼ S13 CS  
BT", bears N.40½°W., 15.8 ft.  
18" dia. D.Fir double blazed and scribed "¼ S18 CS  
BT" bears S.56°E., 42.4 ft.

Ken Hoffine - For: Lone Rock Timberland Co - Nov. 2009 - M160-18  
-----  
Found - 1995 Douglas Co. brass cap at Haines T-iron position  
for quarter corner.  
55" rotted D.Fir stump bears N.85°W., 17.8 ft. as  
per record.  
24" tall D.Fir stump bears N.8°E., 23.7 ft. as per  
record.  
52" D.Fir bears S.10°W., 25.0 ft. as per record.  
14" Maple bears N.40½°W., 15.8 ft. as per record.  
18" tall D.Fir stump bears S.56°E., 42.4 ft. as per  
record.  
Corner lies on 50% Southwest slope recent clear-cut to east  
of corner.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral  
Surveyor, under Group No. 2824, surveyed May 2016/March 2018  
- (DCSO records Vol. 59 Page(s) 23867-8)  
-----  
The ¼ sec. cor of secs. 13 and 18, perpetuated by Haines, in  
1956 and under FB H-102; and further perpetuated by Smith, in  
1995; monumented with an iron post, 1¼" dia. firmly set,  
projecting 10" above ground (alongside of which is a "T"  
shaped iron rod, 3/4" dia., firmly set, projecting 4" above  
ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY  
POINT DRAIN, ORE., with a tack in center) with brass cap  
(properly) mkd. Continued next page

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; & 13, T22-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original bearing trees  
A root hole bears S.55°E., 6.6 ft., alongside of which is  
a decayed fallen maple trunk, size indeterminate, with  
a hollowed blaze.  
A decayed fir stump, 55" dia., bears N.85°W., 17.8 ft.,  
with axe marks visible on bark.  
and the remains of a bearing tree mkd. by Haines  
A sawed decayed fir stump, 26" dia., bears N.9°E., 23.5  
ft., with a healed blaze.  
and the remains of the bearing trees mkd. by Smith  
A sawed decayed fir stump, 20" dia., bears S.54½°E., 42.4  
ft., with a healed blaze.  
A fir, 56" dia., bears S.11¾°W., 24.7 ft., with scribe  
marks ¼ S13 BT visible on bark.  
A maple, 18" dia., bears N.41½°W., 16.0 ft., with a healed  
blaze.