

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T22-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1433)

Set post cor. of secs. 1, 6, 7 and 12, from which
A Maple 12" dia., bears S.58°E., 41 lks. dist.
A Fir 12" dia., bears N.45°E., 44 lks. dist.
A Fir 10" dia., bears N.30°W., 50 lks. dist.
A Fir 8" dia., bears S.72°W., 66 lks. dist.

Wilford N. Haines - For: Chester Swerigen and Harold Woolley
1956 - M 3-22

Corner located by proportional measurement.
Set an angle iron with brass cap at corner point inscribed:
Survey Point Wilford N. Haines #239., from which
12" Fir N.22°30'W., 21.5 ft.
24" Fir S.07°E., 70.8 ft.
24" Fir S.22°30'E., 73.8 ft.
6" Fir N.57°E., 45.9 ft.

Fd. OK, Aug. 1986, D. Branch, M 102-29

Les Roberts, L.S. 1039 - For: Seneca Jones Timber Co. - Dec.
1994 - M 121-27

Corner Report Only
Found - Haines "T" iron set in survey M 3-22
24" Fir, N.17°W., 21.5 ft. (scar vis.) 1956 BT.
36" Fir, S.43°E., 51.5 ft. (rec. S.22°30'E., 73.8')
(scar vis.) 1956 BT.
40" Fir, S.06°E., 45.7 ft. (rec. 70.8') (scar vis.)
1956 BT.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral
Surveyor, under Group No. 2824, surveyed May 2016/March 2018
- (DCSO records Vol. 59 Page(s) 23869-70)

The cor. of secs. 1, 6, 7, and 12, reestablished by Haines,
in 1956, by proportionate measurement; recovered and accepted
by Branch, in 1986; and by Roberts, in 1995; and is accepted
as a careful and faithful reestablishment of the cor
monumented with a "T" shaped iron rod 3/4" dia., firmly set,
projecting 8" above ground, with brass washer mkd. WILFORD N.
HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center,
from which the bearing trees mkd. by Haines
A fir, 14" dia., bears N.37½°E., 17.0 ft., with a healed
blaze.

Continued next page

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T22-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A fir, 42" dia., bears S.43°E., 50.9 ft., with a healed blaze.

A fir, 49" dia., bears S.6½°E., 45.6 ft., with a healed blaze.

A fir, 18" dia., bears S.6½°W., 14.2 ft., with a healed blaze.

Note: the bearing and distance ties to these trees do not match the Haines survey record M3-22 but all have a Haines brass washer attached.

At the corner point Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, directly over the iron rod, 36" long with brass cap mkd.

T 22 S	
R 7 W	R 6 W
S 1	S 6
S 12	S 7
2016	

from which a new bearing tree

A fir, 8" dia., bears N.23½°W., 25.0 ft mkd T22S R7W S1 BT
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.

From the cor., E., 32 ft. dist., to a dirt road, 16 ft. wide, bears N.35°W. and S.25°E., in a curve.