

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1459)

Set ¼ sec. post, from which
A Fir 30" dia., bears N.60°W., 11 lks. dist.
A Fir 8" dia., bears S.52°E., 29 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1483)

The ¼ sec. cor., post badly decayed; bearing trees standing and agree with the description furnished by the surveyor general; at same point I
Set a sandstone 12x10x8 ins., 8" in the ground, for ¼ sec. cor., mkd. ¼ on N. face.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - Sept. 1961 - C.S. File 49/143-68

Found - Haines T-Iron and cap. Rock not found.
Fir tree, now 42", N.60°W., 7.3 ft. Uprooted, down and dead, bark scribing, not original, "¼ S18 BT 363"
Fir tree, now 16", S.52°E., 19.1 ft. uprooted, down and dead, has been chopped open and good scribing "¼S" visible.
27" Maple S.57°W., 109.2 ft. fairly new scribing "¼ S19 BT". Maple is double, diam. measured below fork.
New BT - 4" Fir N.74°E., 70.8 ft. mkd. "¼ S18 CS BT".

Ken Hoffine - for Lone Rock Timber Co. - Dec. 1994 - M 121-43

Found - Haines T-iron w/ washer .5 ft. above ground.
18" D.Fir, bears N.74°W. 17.7 ft., well healed face, we tagged.
14" decaying maple, bears S.57°W. 110 ft. (rec. 109.2') no marks.
13" D.Fir, bears S.22°E. 7.9 ft., we scribed ¼ S.19 B.T. & tagged.
14" D.Fir, bears N.74°E. 70.8 ft., well healed face and B.T. tag.
Corner lies on top of a narrow ridge which runs N.70°E.

continued next page

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2875, surveyed Aug. 2017/Feb. 2019- (DCSO records Vol. 59 Page 23650-1)

The ¼ sec. cor. of secs. 18 and 19, perpetuated by Haines, date unknown, subsequently perpetuated by Godfrey, in 1961; further perpetuated by Hoffine, in 1994; monumented with a "T" shaped iron rod, ¾" dia., firmly set, projecting 9" above ground, with brass washer mkd. WILFORD N. HAINES SURVEY POINT 239 DRAIN, ORE., with a tack in center, (alongside of which is the original sandstone, 6x6x10", lying loose on the ground, mkd. ¼ on one face), from which the remains of a bearing tree mkd. by Godfrey

A sawed fir stump, 22" dia., bears N.72¾°E., 70.7 ft., with a healed blaze.

and a bearing tree mkd. by Hoffine

A fir, 19" dia., bears S.20¼°E., 7.8 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½" dia., 24" in the ground, directly over the iron rod, 36" long, with brass cap mkd.

T22S R6W

¼ S 18
S 19
2017

from which

A fir, 13" dia., bears N.32¾°E., 3.0 ft., mkd. ¼ S18 BT. Bury the original sandstone alongside the stainless steel post.