

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION C C for Secs. 31 & 32, So. bdy

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1492)

-----  
At point of intersection, I  
Set a sandstone, 12x10x8 ins., 8" in the ground, for a closing cor. of secs. 31 and 32, mkd. C C on N. with 5 grooves on E. and 1 groove on W. faces; from which  
A Cedar 12" dia., bears N.14°E., 13 lks. dist., mkd. T22S R6W S32 BT.  
A Fir 24" dia., bears N.33°W., 40 lks. dist., mkd. T22S R6W S31 BT.  
This cor. is on a N. slope 50 ft. above foot of ascent.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12631-32)

-----  
The closing cor., determined at record bearing and distance from the remains of the original bearing trees:  
A Cedar snag, burned, bears N.14°E., 13 lks. dist.  
A stump hole, bears N.33°W., 40 lks. dist., with fallen log mkd. T22 on exposed and burned blaze.  
At the corner point  
Set an iron post, 3 ft. long, 2" dia., 18" in the ground to solid rock, and in a mound of stone, 6 ft. base, to top, with brass cap mkd:  
C C  
T22SR6W  
S31|S32  
S 6  
1955

Wilford N. Haines - For: Irvin Rice and Whipple Mill - 1954-55 C.S. File 42/13

-----  
Found 2 BTs. At point for corner, Set an angle iron with brass cap inscribed Survey Point-Wilford N. Haines No. 239.

Wilford N. Haines - June 29, 1962 - C.S. File 51/222-3

-----  
Found - My corner T-Iron with GL0 brass cap alongside in a pile of rocks.  
18" Fir BT, N.36½°W., 45.4 ft.  
24" Fir stump scribed CC S32 BT, N.20°E., 48.1 ft.

(Cont. Next Page)

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION C C for Secs. 31 & 32, So. bdy

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - Dec. 23, 1969 - C.S. 49/143-99

-----  
Found - 1955 Cadastral brass cap, nearly out of ground, properly mkd., with Haines T-Iron alongside.  
18" Fir N.36½°W., 45.4 ft., now dead, scribe visible, overgrowth of 9 rings. Haines BT  
24" Fir stump N.20°E., 48.1 ft., scribe visible. Haines BT. (Cont. Next Page)  
Orig. Cedar BT gone. Stumphole and turned out tree to NW still in evidence.

We Reset Brass Cap.

New BT - 12" Hemlock N.6°W., 47.8 ft. mkd. T22S R6W S31 CC CS BT.

No trees close to NE. This corner lies on very steep northerly slope about 350 ft. South of Squaw Creek.

Survey by Ken Hoffine, L.S. #2291 - Gary Aniolet, wit. - For: Lone Rock Timber Co. - March/Nov. 1990 - C.S. File 63/127-5

-----  
Found - Corner is a GLO brass cap with Haines T-Iron alongside. Corner is loosely set in rock.  
12" W.Fir (Rec. Hemlock) bears N.6°W., 47.6 ft., well healed face and BT tag.

New BT - Put Lone Rock Timber location tag on 6" D.Fir bearing N.60°E., 24.4 ft.

Painted faces and wrote BT on tree trunks of BTs with flourescent orange paint. Cor. lies on steep N. slope near rock face with pile of rocks around corner and Haines T-Iron alongside. Small stand of 20-40" timber to the NW and Squaw Creek bears North approx. 165 ft.

Fd. OK, March 1991, M 111-72