

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1491-92)

Set a Fir post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor. mkd. ¼ S on W. face, from which

A Fir 24" dia., bears N.39°E., 20 lks. dist. mkd. ¼ S BT.

A Fir 20" dia., bears S.79°W., 84 lks. dist. mkd. ¼ S BT.

This cor. is on the westerly slope of spur, 50 ft. above creek.

Wilford N. Haines - For: E.G. Whipple Mill - File Jan. 15, 1959 - M 13-66

Set Lot Marker 1" x 1" x 36" T Iron with cap inscribed "Survey Point-Wilford N. Haines #239" from old BTs. Scribed - 10" Fir N.32°W., 13.51 ft.

Fd. OK, May 1990, Ken Hoffine, C.S. File 63/104-32

Fd. OK, April 1997, Ken Hoffine, C.S. File 65/13-8