

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1488-89)

Set a sandstone, 14x12x8 ins., 9" in the ground, for cor. of secs. 29, 30, 31 and 32, mkd. with 1 notch on S. and 5 notches on E. edges; from which

A Cedar 14" dia., bears N.31°E., 90 lks. dist. mkd. T22S R6W S29 BT.

A Fir 42" dia., bears S.83°E., 46 lks. dist. mkd. T22S R6W S32 BT.

A Fir 36" dia., bears S.74°W., 13 lks. dist. mkd. T22S R6W S31 BT.

A Fir 48" dia., bears N.35°W., 43 lks. dist. mkd. T22S R6W S30 BT.

This cor. is on the SW. slope of ridge, 125 ft. below top.

Wilford N. Haines - For: E.G. Whipple Mill - 955 - Map made Jan. 1956 - M 2-13

Found old BTs.

Set angle iron with brass cap inscribed "Survey Point-Wilford N. Haines 239".