

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1488)

Set a sandstone, 18x14x8 ins., 13" in the ground for ¼ sec. cor. mkd. ¼ on W. face; from which
 A Chincapin 8" dia., bears S.40°E., 53 lks. dist. mkd. ¼ S BT.
 A Fir 42" dia., bears N.45°W., 40 lks. dist. mkd. S BT.

Wilford N. Haines - For: E.G. Whipple Mill - 1955 - Map made Jan. 1956 - M 2-13 (and H-105 for BTs)

Found - Orig. 42" Fir N.45°W., 40 lks., is now a snag, but scribe visible.
Set angle iron with brass cap inscribed "Survey Point-Wilford N. Haines 239, from which
 18" R.Fir, N.65°45'W., 12.60 ft.
 6" R.Fir, N.78°45'E., 11.75 ft.