

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1458)

 Set post cor. to secs. 17, 18, 19 and 20, from which
 A Cedar 30" dia., bears N.10°E., 21 lks. dist.
 A Hemlock 24" dia., bears S.20°E., 30 lks. dist.
 A Cedar 24" dia., bears S.2°W., 36 lks. dist.
 A Maple 6" dia., bears N.45°W., 50 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1483)

 The Sec. cor., post decayed; bearing trees all standing and agree with the description furnished by the surveyor general; at same point, I
 Set a sandstone, 16x10x6 ins., 11" in the ground, for cor. of secs. 17, 18, 19 and 20, mkd. with 5 notches on E. and 3 notches on S. edges.

Wilford N. Haines - Field Book, H-120 (date?)

 48" Fir N.32°E., 94.4 ft.
 28" Maple S.43°W., 60.5 ft.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - Aug./Sept. 1961 - C.S. File 49/143-67

 Found - Haines "T" iron and cap and sandstone rock with notches as described. Rock unearthed and fallen over.
 Cedar tree, 48", N.10°E., 14 ft. (to face) Portions of old scribing found on badly rotted face. Tree hollowed out by fire, nearly dead.
 Badly burned Cedar snag S.2°W., 23.8 ft. No scars or scribing.
 No trace of NW or SE BTs.
 24" Maple S.37°W., 60.3 ft. scribed recently, "T22S R6W S19 BT 363"
 50" D.Fir N.31°E., 94.8 ft. scribed in wood, scribing covered with pitch, except "363"
 New BTs -12" Cedar S.68°E., 28.5 ft. mkd. T22S R6W S20 CS BT
 17" Maple N.14½°W., 91.2 ft. mkd. T22S R6W S18 CSBT

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #891, surveyed April/June 1976 (DCSO records Vol. 39 Page(s) 15940)

The Sec. cor., perpetuated and recorded by Haines in 1958, and further perpetuated by Godfrey in 1961, monumented with a 3/4" "T" shaped iron rod, firmly set, projecting 4" above ground, with an alum. washer mkd. RLS 239, with a sandstone, 16 x 10 x 6 ins., with 5 notches on E. and 3 notches on S. face, firmly set, projecting 8" above ground, alongside, from which the remains of the original bearing trees:

A Cedar 48" dia., bears N.9½°E., 24½ lks. dis. with scribe marks T BT visible on decayed blaze. (Rec. 21 lks.)

A Cedar snag 30" dia., bears S.14°W., 40 lks. dist., no marks visible on decayed blaze.

and bearing trees mkd. by Haines

A Fir 48" dia., bears N.31½°E., 144 lks. dist., with healed blaze.

A Maple 30" dia., bears S.38°W., 92 lks. dist. with scribe marks 6W S19 B visible on open blaze.

and bearing trees mkd. by Godfrey

A Cedar 15" dia., bears S.68¼°E., 44 lks. dist., with healed blaze.

A Maple 15" dia., bears N.12½°W., 139 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22	S R 6 W
S 18	S 17
S 19	S 20
1976	

Reset "T" shaped iron rod and stone alongside iron post.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2875, surveyed Aug. 2017/Feb. 2019- (DCSO records Vol. 59 Page 23650)

The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground, with a brass cap (properly) mkd. from which the remains of an original bearing tree

A hollow, broken cedar snag, bears N.9½°E., 16.2 ft., alongside of which is the down trunk segment, 50" dia., no marks visible.

and the BTs mkd. by Haines, in field tablet FB H-120

A fir, 52" dia., bears N.31½°E., 95.0 ft., with illegible scribe marks visible on bark.

continued next page

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A maple, 36" dia., bears S.38°W., 60.7 ft., with a healed blaze.

and the BTs mkd. by Godfrey in 1961

A cedar, 36" dia., bears S.68¼°E., 29.0 ft., with a healed blaze.

A maple, 26" dia., bears N.12½°W., 91.7 ft., with a healed double blaze.

and a bearing tree mkd. by person(s) unknown

A vine maple, 9" dia., bears N.88°W., 17.5 ft., with a healed double blaze.

Corner is located E., 65 ft., of a creek, 3 ft. wide, course N. 15° E.

NAD 1983 (2011)

Latitude: 43°38'58.20" N Longitude: 123°26'52.99" W.