

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1452)

-----  
Set ¼ sec post, from which  
    A W.Oak, 30" dia., bears N.64°W., 325 lks.  
    A W.Oak, 20" dia., bears N.4¼°E., 872 lks.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - 1961-1962 - C.S. File 49/143-2

-----  
Corner not found.

David Edwards; surveyed for Dick Hess May 1997 - C.S. 65/12-8

-----  
Set - 5/8" x 30" steel pin w/red plastic cap mkd. "D.A. Edwards-LS 2339"

New Accessories -

    15" dia. Fir bears N.34°20'E., 56.54 ft.  
    15" dia. Fir bears S.6°59'E., 75.72 ft.  
    12" dia. Fir bears S.79°16'W., 21.61 ft.  
    11" dia. Fir bears N.47°56'W., 49.60 ft.