

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1485)

Set a post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face; from which

A Fir 30" dia., bears N.48°E., 213 lks. dist. mkd. ¼ S BT

A Fir 12" dia., bears S.60°W., 210 lks. dist. mkd. ¼ S BT

This cor. is on the southerly slope of spur, 50 ft. above ravine.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #1073, surveyed Aug/Sept. 1981 (DCSO records Vol. 44 Page(s) 17031)

The ¼ sec. cor., perpetuated by Wilford N. Haines, LS. #239, during an unrecorded survey, date unknown, monumented with a 3/4" "T" shaped iron rod, firmly set, projecting 4" above ground, with an alum. washer mkd. RLS 239, from which the remains of an original bearing tree

A sawed Fir stump 52" dia., bears S.60°W., 210 lks. dist. with scribe marks ¼ SBT visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S R 6 W
¼ S 20
S 29
1981

from which new bearing trees

A Fir 17" dia., bears N.63°E., 20½ lks. dist. mkd. ¼ S20 BT.

A Fir 10" dia., bears s.60°W., 23 lks. dist. mkd. ¼ S29 BT.