

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1458)

-----  
Set ¼ sec. post, from which  
A Fir 24" dia., bears N.30°E., 28 lks. dist.  
A Fir 24" dia., bears S.50°E., 10 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664 dated May 23, 1896 (DCSO records Vol. 44 Page(s) 1483)

-----  
¼ sec. cor., which is a post, 4" sq., 18" above ground, mkd. and witnessed as described by the surveyor general.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #891, surveyed April/June 1976 (DCSO records Vol. 39 Page(s) 15939)

-----  
Point for the ¼ sec. cor., determined by the method of broken boundaries; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼  $\frac{S\ 17}{S\ 20}$   
T 22 S R 6 W  
1976

from which

A Fir 4" dia., bears N.35½°W., 23½ lks. dist. mkd. ¼ S17 BT.

A Fir 7" dia., bears S.54°E., 13 lks. dist. mkd. ¼ S20 BT.