

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 300277

PRIMARY CORNER DESCRIPTION E. Sec. cor. for secs. 20 & 29 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1486)

At point of intersection, I
Set Cedar post, 3 ft. long, 4" sq., 24" in the ground, for a closing cor. of secs. 20 and 29, mkd. C C T22S R6W on W.; S20 on N.; and S29 on S. face; with 2 grooves on S. face, from which

A Fir 60" dia., bears S.24°W., 87 lks. dist. mkd. T22S R6W S29 BT.

A Fir 16" dia., bears N.70°W., 100 lks. dist. mkd. T22S R6W S20 BT.

This cor. is on a southwesterly slope, 100 ft. above creek.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - Aug. 1961 - C.S. File 49/143-59

Found - At corner, found Haines T-Iron and cap.
Fir snag, now 34", N.70°W., 66.0 ft. Has been previously opened and good scribing "S20" visible.

No trace found of SW BT.

New BTs -9" W.Fir N.63°W., 31.7 ft. mkd. T22S R6W S20 CS CC BT.

14" R.Cedar N.75½°E., 35.9 ft. mkd. CC S20 S29 CS BT

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #1073, surveyed Aug/Sept. 1981 (DCSO records Vol. 44 Page(s) 17032)

Point for the closing cor. of secs. 20 and 29.
Set an alum. post, 28" long, 2½" dia., 24" in the ground, with alum. cap mkd:

T 22 S R 6 W
CC $\frac{S 20}{S 29}$ | S 28
1981

from which

A Fir 5" dia., bears S.46°W., 28 lks. dist. mkd. X BT.

A W.Fir 8" dia., bears N.42°W., 61 lks. dist. mkd. T22S R6W S20 BT.

From this point, the orig. closing cor. of secs. 20 and 29, perpetuated by Haines during an unrecorded survey, date unknown, and perpetuated and recorded by Godfrey in 1961, bears N.87°44'E., 0.03 chs. dist., monumented with a 3/4" "T" shaped iron rod, firmly set, projecting 4" above ground, with an alum. washer mkd. RLS 239, (Cont. Next Page)

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 300277

PRIMARY CORNER DESCRIPTION E. Sec. cor. for 20 and 29 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of an original bearing tree
A Hemlock stump 20" dia., bears N.70°W., 100 lks. dist.,
alongside of which is lying a Hemlock log, with scribe
marks 22 R6 S20 visible on opened blaze.
and bearing trees mkd. by Godfrey
A Cedar 14" dia., bears N.75°E., 54½ lks. dist. with
scribe marks CC S20 S29 CS BT visible on open blaze.
A W.Fir 16" dia., bears N.63½°W., 48 lks. dist., with
healed blaze.
From this same point, the cor. of secs. 21 and 28, bears
N.0°47'W., 2.19 chs. dist.