

PRIMARY CORNER DESCRIPTION W. Sec. cor. for Secs. 21 and 28 only

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1455-56)

-----  
Set post cor. to secs. 20, 21, 28 and 29, from which  
A Fir 30" dia., bears N.2°E., 15 lks. dist.  
A Dogwood 8" dia., bears S.28°E., 35 lks. dist.  
A Fir 48" dia., bears S.30°W., 31 lks. dist.  
A Fir 50" dia., bears N.62°W., 34 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1482 and 1485-86)

-----  
(Page 1482)  
Orig. cor., post decayed; some of the bearing trees down; those standing agree with the description furnished by the surveyor general.  
(Pages 1485-86)  
From the cor. of secs. 20, 21, 28 and 29, before described which I reestablish at same point as follows:  
Set a Hemlock post 3 ft. long, 4" sq., 24" in the ground, for cor. of secs. 21 and 28, mkd. T22S S21 on NE.; and R6W S28 on SE.; with 4 notches on E. and 2 notches on S. edges; from which  
A Hemlock 5" dia., bears N.54°E., 6 lks. dist. mkd. T22S R6W S21 BT.  
A Dogwood 8" dia., bears S.18°E., 39 lks. dist. mkd. T22S R6W S28 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & C. Putnam, crew - Aug. 21, 1961 - C.S. File 49/143-58

-----  
Corner Report Only  
Found - Haines "T" Iron and cap.  
No trace of orig. BTs found. Either 1871 or 1897 surveys.  
34" Cedar N.48°W., 47.0 ft. An old scar has been opened and scribing "20" visible in opening, old face covered with 50 to 60 years overgrowth.  
24" Fir N.84°E., 17.4 ft. Recently bark scribed "T22S R6W S21 BT"

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #1073, surveyed Aug/Sept. 1981 (DCSO records Vol. 44 Page(s) 17028-29)

-----  
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION W. Sec. cor. for Secs. 21 & 28 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

The sec. cor., perpetuated by Haines, during an unrecorded survey, date unknown, monumented with a 3/4" "T" shaped iron rod, firmly set, projecting 4" above ground, with an alum. washer mkd. RLS 239, from which the remains of three original bearing trees

A root hole bears N.2°E., 15 lks. dist., with the remains of a down Fir alongside, size indeterminate, no marks visible.

A root hole, bears S.30°W., 31 lks. dist., with the remains of a down Fir alongside, size indeterminate, no marks visible.

A root hole bears N.62°W., 34 lks. dist. with the remains of a down Fir alongside, size indeterminate, no marks visible. (Cont. Next Page)

and the remains of a bearing tree mkd. by Nicklin

A root hole bears N.54°E., 6 lks. dist., with the remains of a down Hemlock, size indeterminate, no marks visible.

At the corner point

Set an alum. post, 28" long, 2 1/2" dia., 24" in the ground, with alum. cap mkd:

	T	22	S	R	6	W
	S	20		S	21	
				S	28	
				1981		

from which new bearing trees

A W.Fir 8" dia., bears N.41¼°E., 62½ lks. dist. mkd. T22S R6W S21 BT.

A Fir 7" dia., bears S.31°E., 11 lks. dist. mkd. T22S R6W S28 BT.

Deposit the "T" iron alongside the iron post.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2875, surveyed Aug. 2017/Feb. 2019- (DCSO records Vol. 59 Page 23646-7)

-----  
 The cor. of secs. 21 and 28 only, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, (alongside of which is a "T" shaped iron rod, ¾" dia., firmly set, projecting 2" above ground, with brass washer mkd. WILFORD N. HAINES SURVEY POINT 239 DRAIN, ORE., with a tack in center) with a brass cap mkd.

from which the remains of a BT mkd. by Jelley in 1981

A sawed fir stump, 15" dia., bears S.31°E., 7.3 ft., with a healed blaze.

and new bearing trees

A fir, 15" dia., bears N.80¾°E., 30.1 ft., mkd. T22S R6W S21 BT.

Continued next page

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION W. Sec. cor. for Secs. 21 and 28 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 6" dia., bears S. 40° E., 3.8 ft., mkd. X BT.  
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at  
the base right side-center & each corner established or  
remonumented has a magnet deposited in a white plastic case  
at the base of the stainless steel post. Alum. Angle iron  
driven alongside each monument.

NAD 1983 (2011)

Latitude: 43°38'09.77" N      Longitude: 123°25'42.68"W.