

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1448)

Set post cor. of secs. 16, 17, 20 and 21, from which
A Fir 15" dia., bears N.5°E., 25 lks. dist.
A Fir 15" dia., bears N.40°W., 47 lks. dist.
A Fir 40" dia., bears S.32°E., 69 lks. dist.
A Dogwood 10" dia., bears S.35°W., 30 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & C. Putnam, crew - Aug/Sept 1961 - C.S. File 49/143-72

Found - Fir tree, now 45" S.32°E., 45.5 ft. Has been chopped open and good scribing "6W" visible on exposed face.

Fir tree, now 32" N.5°E., 16.5 ft. shows good scar.
No trace of SW BT.

A 26" W.Fir stands at location for corner.

Set Iron pipe with brass cap alongside mkd.

County Surveyors Office

T 22 S R 6 W

S 17 | S 16

S 20 | S 21

1961

New BTs -8" Fir S.22°E., 20.5 ft. mkd. T22S R6W S21 CS BT.

9" Chinquapin N.10°W., 25.8 ft. mkd. T22S R6W S17 CS BT.

7" Fir N.50°E., 49.0 ft. mkd. T22S R6W S16 CS BT.

10" Hemlock S.16°W., 45.2 ft. mkd. T22S R6W S20 CS BT.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #517, surveyed Aug/Sept. 1963 (DCSO records Vol. 32 Page(s) 13455-56)

The Sec. cor., recovered and recorded by Godfrey in 1961, monumented with a corner tree, a Fir, 26" dia., mkd. with a healed blaze on the N. S., E., and W. sides. I REMARK this tree, T22S S16 on NE. side, R6W S21 on SE. side, S20 on SW. side, and S17 on NW. side, from which the remains of the original bearing trees

A Fir 32" dia., bears N.5°E., 25 lks. dist. mkd. with a healed blaze.

A Fir 45" dia., bears S.33½°E., 72 lks. dist. 69 lks. dist. to face, mkd. W 6 on opened blaze. (Rec. S.32°E., 69 lks.)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 40" dia., bears N.37½°W., 47 lks. dist. no marks visible on opened blaze. (Rec. bearing N.40°W.) and bearing trees by Godfrey
A Fir 7" dia., bears N.50°E., 74 lks. dist. mkd. with partially healed double blaze.
A Fir 8" dia., bears S.21 3/4°E., 31 lks. dist., mkd. with partially healed double blaze.
A Hemlock 10" dia., bears S.16°W., 69 lks. dist., mkd. T22S R6W S20 CS BT on double blaze.
A Chinquapin 9" dia., bears N.10½°W., 39 lks. dist., mkd. T22S R6W S17 CS BT on double blaze.
From this point, an I.Post 1½" dia., protruding 10" above the ground, bears West, 4 lks. dist. with 1961 DCSO brass cap.

Corner found and used in BLM resurvey by James E. Jelley, Group #891, surveyed 1976, (DCSO records, Vol. 39 Page 15937)

Corner found and used in BLM resurvey by James E. Jelley, Group #1073, surveyed 1981 (DCSO records, Vol. 44 Pages 17029-30)

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2875, surveyed Aug. 2017/Feb. 2019- (DCSO records Vol. 59 Page 23647-8)

The cor. of secs. 16, 17, 20, and 21, monumented with the remains of the cor. tree, a heavily decayed grand fir stump, size indeterminate, with no marks visible, from which the remains of the original bearing trees

A fir, 52" dia., bears S.33½°E., 47.5 ft., with no marks visible on partially healed blaze.

A fir, 50" dia., bears N.37½°W., 31.0 ft., with no marks visible on partially healed blaze.

A sawed fir stump, 32" dia., bears N.4¾°W., 16.5 ft., with a healed blaze. (Record, N.5°E.) and the accessories mkd. by Godfrey, in 1961, filed as CS49/143-67, reported by Beck

A fir, 25" dia., bears N.50°E., 48.8 ft., with a healed blaze.

A fir, 17" dia., bears S.15½°E., 20.5 ft., with a healed blaze. (Record, S.21¾°E.)

An iron post, 1½" dia., firmly set, projecting 12" above ground, bears West, 2.64 ft., with a brass cap mkd. COUNTY SURVEYORS OFFICE T22S R6W S16 S17 S20 S21 1961.

At the corner point

continued next page

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd.

T 22 S R 6 W
S 17 | S 16
S 20 | S 21
2017

from which a new bearing tree

A fir, 4" dia., bears S.49¾°W., 66.1 ft., mkd. T22S R6W S20 BT.

From the cor., a point established by Godfrey, Douglas County Deputy Surveyor, in 1961, filed as CS 49/143-67, bears West, 2.64 ft., monumented with an iron post, 1½" dia., firmly set, projecting 12" above ground, with a brass cap mkd. COUNTY SURVEYORS OFFICE T22S R6W S16 S17 S20 S21 1961.

At the request of the Douglas County Surveyors Office, remove the brass cap and upper 8 ins. of the iron post, leaving the remainder in its original position, and place a yellow plastic cap, 1 1/2" dia. inside the iron post, mkd. DOUG CO SURVEYOR. Bury the brass cap alongside the stainless steel post.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.