TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1448)

Set post cor. of secs. 8, 9, 16 and 17, from which
A Redwood 12" dia., bears S.56°E., 46 lks. dist.
A Fir 36" dia., bears S.35°W., 42 lks. dist.
A Fir 30" dia., bears N.15°W., 30 lks. dist.
A W.Oak 14" dia., bears N.26°E., 62 lks. dist.

Survey by George Scroggin for plat of Sunnydale Orchards, Aug. 6, 1914 - Plat Vol. 5 Page 20 A&B

Bolt.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & C. Putnam, crew - Sept/Oct 1961 - C.S. File 49/143-83

Found - Iron bolt 3/4" dia., with square head 1¼" sq.
Fir snag 36", S.35°W., 27.7 ft. No scar or scribing visible.
Fir log, nearly buried in fill, base of which bears N.15°W., 19.8 ft.
Remnants of Cedar stump bears S.56°E., 30.4 ft. Too far gone to find scars or scribing.
No trace of NE BT.

Alongside Bolt, Set Brass cap at cor. mkd:

County Surveyors Office
T 22 S R 6 W
S 8 | S 9
S 17 | S 16
1961

New BTs -8" W.Oak N.10°E., 7.6 ft. mkd. T22S R6W S9 CS BT.
7" Maple, in clump of Maple, N.49°W., 32.5 ft. mkd. T22S R6W S8 CS BT.
8" W.Oak S.66½°W., 31.7 ft. mkd. T22S R6W S17 CS BT
14" Ash S.73½°E., 28.1 ft. mkd. T22S R6W S16 CS BT.

Corner lies approx. 100 ft. South of centerline of Hwy. #38.

Corner Fd. and used in BLM resurvey by James E. Jelley, under Group #891, surveyed April/June 1976 (DCSO records, Vol. 39 Pages 15938-39)

Fd. OK, Aug. 2000 by D. Edwards, - M135-36

DCSO-GIS Corner visitation - 7/27/2005 - Typed: 1/19/2011 - C.S. File 67/33-1

Monument - 2½" BC on 1¼ IP. Comment - (needs) rehab