

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1449)

-----  
Set ¼ sec. post, from which  
    A W.Oak 36" dia., bears S.66°W., 140 lks. dist.  
    A W.Oak 36" dia., bears S.38°E., 93 lks. dist.

Survey by George Scroggin - For: Plat of Sunnydale Orchards, Aug. 6, 1914 - Plat Vol. 5 Page 20 A&B

-----  
Bolt.

H. L. Eppstein, County Surveyor - Wit: M.C. Bowker; Philip Snell; Don Blackford - June 26, 1924 - Vol. 3 Page 187

-----  
Renew from fallen BTs. Set a 3/4" round iron bar 18" long, from which  
    A 24" W.Fir bears N.76°W., 18.2 ft. dist.  
    A 18" W.Fir bears N.61½°E., 17 ft. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - Aug. 1961 - C.S. File 49/143-39

-----  
Found - 3/4" x 18" iron rod set by Eppstein in 1924.  
    1/2" Iron pipe alongside iron rod.  
    Rotted remnant of stump N.76°W., 18.2 ft.  
    Rotted remnant of stump N.61½°E., 17.0 ft.  
Both stumps too far tone to find any trace of scribing or axe marks.  
Set brass cap mkd: County Surveyors Office, 1961 T22S R6W ¼ S8|S9.  
New BTs -6" D.Fir N.28°W., 50.8 ft. mkd. ¼ S8 CS BT.  
    6" D.Fir N.46°E., 96.0 ft. mkd. ¼ S9 CS BT.  
Fence corner, fences W. and S., bears West, 23.5 ft.

Fd. OK, Aug. 2000 by D. Edwards, - M135-36