

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION South ¼ Cor. Sec. 33 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor  
Under Group No. 2653, Surveyed June/July 2012 - DCSO records  
Vol. 58 Page(s) 22978

-----  
Point for the ¼ sec. cor. of sec. 33 only, on the S. bdy. of  
the Tp., at midpoint bet. the closing cor. of secs. 32 and 33  
and the closing cor. of secs. 33 and 34.  
Set a stainless steel post, 28" long, 2½" dia., 26" in the  
ground, with brass cap mkd.

T22S R6W  
¼ S 33  
T23S R6W  
2012

from which  
A fir, 19" dia., bears N.72½°E., 32.0 ft. mkd. ¼ S33 CC BT  
A fir, 19" dia., bears N.48¾°W., 27.6 ft. mkd. ¼ S33 CC BT  
Bury a magnet in a white plastic case at the base of the  
stainless steel post.  
Corner is located on a SW. slope, 130 ft. W. of a ridge,  
bears N.10°E. and S.10°W.