

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1456)

Set ¼ sec. post, from which
A Fir 16" dia., bears North, 30 lks. dist.
A Fir 12" dia., bears S.20°W., 16 lks. dist.

Wilford N. Haines - Field Book, H-106

BT Sect 21, 36" D.Fir, bark scribe.
Scribed 14" D.Fir "¼ S28 BT 239", S.46°E., 41.9 ft.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & C. Putnam, crew - Aug. 10, 1961 - C.S. File 49/143-47

Corner Report Only
Found - Haines "T" Iron and cap, from which
An uprooted tree to the North and a partially rotted stump to the SW. Approximately fit descriptions of orig. BTs. No scars or scribing found on these.
A 34" Fir tree bark scribed "¼S BT 363" bears N.39°E., 30.3 ft.
A 24" Fir tree bears S.48°E., 35.9 ft. This tree has scribing in wood. Cannot make out letters. Too much pitch.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2875, surveyed Aug. 2017/Feb. 2019- (DCSO records Vol. 59 Page 23646)

The ¼ sec. cor. of secs. 21 and 28, perpetuated by Haines, in field tablet FB H-106; from original evidence no longer in existence; monumented with a "T" shaped iron rod, ¾" dia., firmly set, projecting 8 ins. above ground, with brass washer mkd. WILFORD N. HAINES SURVEY POINT 239 DRAIN, ORE., with a tack in center, from which the remains of the bearing trees mkd. by Haines

A tin-capped, sawed fir stump, 36" dia., bears N.37¾°E., 29.7 ft., no marks visible.
A decayed fir stump, 26" dia., bears S.44¼°E., 36.3 ft., no marks visible.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 27" in the ground, directly over the iron rod, 32 ins. long, with brass cap mkd.

Continued next page

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

T22S R6W
 $\frac{1}{4}$ $\frac{S\ 21}{S\ 28}$
2017

from which a new bearing tree
A fir, 14" dia., bears N.75 $\frac{3}{4}$ °W., 50.1 ft., mkd. $\frac{1}{4}$ S21 BT.
Each new BT has a 2 $\frac{1}{2}$ "x $\frac{1}{4}$ " magnetic nail (Mag Nail) driven at
the base right side-center & each corner established or
remonumented has a magnet deposited in a white plastic case
at the base of the stainless steel post. Alum. Angle iron
driven alongside each monument.