

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Pg 1455)

Set a Post cor. to secs. 27, 28, 33 and 34, from which
 A Yew 4" dia., bears N.30°E., 11 lks. dist.
 Dogwood 8" dia., bears S.80°E., 47 lks. dist.
 A Fir 24" dia., bears S.30°W., 19 lks. dist.
 A Fir 6" dia., bears N.15°W., 15 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1476-77)

The Sec. cor., post badly decayed, some of the bearing trees down; I reestablished this cor. at the point as follows:
 Set a Hemlock post, 3 ft. long, 4" sq., 24" in the ground, for sec. cor., mkd. T22S S27 on NE.; R6W S34 on SE.; S33 on SW.; and S28 on NW. faces; with 3 notches on E. and 1 notch on S. edges; from which
 A Yew 6" dia., bears N.30°E., 11 lks. dist. mkd. T22S R6W S27 BT.
 A Maple 8" dia., bears S.72½°E., 19 lks. dist. mkd. T22S R6W S34 BT.
 A Hemlock 20" dia., bears S.30°W., 19 lks. dist. mkd. T22S R6W S33 BT.
 A Maple 8" dia., bears N.15°W., 15 lks. dist. mkd. T22S R6W S28 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & C. Putnam, crew - Aug. 11, 1961 - C.S. File 49/143-48

Found - Maple tree, now 20", S.72½°E., 12.5 ft. Tree hollow on back. Reverse scribing visible through opening "W S34 BT".

No trace of other original BTs.

Set Brass cap at cor. mkd: County Surveyors Office

T	22	S	R	6	W	
		S	28		S	27
		S	33		S	34
						1961

Found three trees scribed within past 10 years:

- 10" Hemlock S.62°W., 12.0 ft. scribing visible "S33 T22 R6W BT 239".
- 16" R.Cedar N.14°E., 13.0 ft. scribing visible "27 22 6 BT 39".
- 10" Hemlock N.62°E., 25.4 ft. scribing visible "S27 T22S R6W BT 239".

CONT.

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2500, Surveyed July/Aug. 2010 - (DCSO records Vol. 57 Page(s) 22809 & Survey plat 2012-1)

The cor. of secs. 27, 28, 33, and 34, perpetuated by Godfrey, in 1961, monumented with an iron post, 1¼" dia., firmly set, projecting 11" above ground, with a brass cap (properly) mkd. from which a bearing tree mkd, by Nicklin

A maple, 19" dia., bears S.72½°E., 2.5 ft., with reverse scribe marks T W S 34 BT visible on interior of blaze. and the remains of bearing trees mkd. by person(s) unknown, reported by Godfrey

A cedar, 29" dia., bears N.4¾°E., 12.7 ft., with a healed blaze.

A hemlock, 18" dia., bears N.62°E., 25.5 ft., with a healed blaze.

A roothole bears S.63½°W., 11.0 ft., downhill of which is an uprooted, decayed hemlock, 16" dia., with a healed blaze.

and new bearing trees

A cedar, 18" dia., bears S.36½°W., 21.6 ft., mkd. T22S R6W S33 BT.

A hemlock, 6" dia., bears N.76¾°W., 32.5 ft., mkd. X BT. Corner is located on a steep N slope, 185 ft. S. of a ravine, drains S.80°E.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2653, Surveyed June/July 2012 - DCSO records Vol. 58 Page(s) 22985

The cor. of secs 27, 28, 33, and 34, monumented with an iron post, 1¼" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd.

from which the remaining bearing tree mkd. by Nicklin

A hollow maple, 19" dia., bears S.72½°E., 12.5 ft., with reverse scribe marks T W S34 visible on the inside. and remains of bearing trees mkd. by person(s) unknown

A cedar, 30" dia., bears N.14¾°E., 12.7 ft., with a healed blaze.

A hemlock, 18" dia., bears N.62°E., 25.5 ft., with a healed double blaze.

A roothole bears S.63½°W., 11.0 ft., downhill of which is a fallen, decayed hemlock snag, 16" dia., with no marks visible.

and bearing trees mkd. by Saveland

A cedar, 19" dia., bears S.36½°W., 21.6 ft., with scribe marks T22S R6W S33 BT visible on an open blaze.

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A hemlock, 6" dia., bears N.76 $\frac{3}{4}$ °W., 32.5 ft., with scribe marks X BT visible on an open blaze.

NAD 1983 (CORS 96)

Latitude: 43°37'17.03"N

Longitude: 123°24'29.45"W