TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1454)

Set ¼ sec. post, from which
A Laurel 6" dia., bears N.85°E., 7 lks. dist.
A Fir 30" dia., bears S.85°W., 25 lks. dist.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #517, surveyed Aug/Sept. 1963 (DCSO records Vol. 32 Page(s) 13449-50)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼
S21 | S22
T 22 S R 6 W
1963

from which
A Fir 6" dia., bears N.46°E., 47 lks. dist. mkd. ¼ S22 BT.
A Fir 7" dia., bears N.5°W., 21 lks. dist. mkd. ¼ S21 BT.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2875, surveyed Aug. 2017/Feb. 2019- (DCSO records Vol. 59 Page 23644)

The ¼ sec. cor. of secs. 21 and 22, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with a brass cap (properly) mkd.
from which the remains of a bearing tree mkd. by Beck in 1963
A fir, 28" dia., bears N.5°W., 13.9 ft., with a healed blaze.
and a new bearing tree
A fir, 4" dia., bears N.71½°E., 21.5 ft., mkd. X BT.
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.