

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1445)

Set post cor. of secs. 15, 16, 21 and 22, from which
A Willow 4" dia., bears S.18°W., 21 lks. dist.
A Maple 4" dia., bears N.85°W., 51 lks. dist.
A Fir 3" dia., bears N.55°E., 29 lks. dist.
A Fir 15" dia., bears S.45°E., 111 lks. dist.

Ben B. Irving, Deputy Co. Surveyor - Wit: W.S. Crear; George Montgomery - Jan. 1928 - C.S. File 22/25

Found - Chopped out old BT, 40" Fir S.45°E., 111 lks. dist., scribe plain.
The burned out stump of an old Maple, bears N.85°W., 41 lks. This may be remains of an old BT as the orig. field notes call for a Maple N.85°W., 51 lks.

Set 8" x 6" x 20" sandstone for corner chiseled X ¼ and having 3 notches on each face.

BTs - An 8" Fir bears N.40°W., 41 lks. dist. scribed T22S R6W S16 CS BT.
A 14" Fir bears N.85°E., 52 lks. dist. scribed T22S R6W S15 CS BT.
A 15" Fir bears S.15°E., 48 lks. dist. scribed T22S R6W S22 CS BT.
A 16" Fir bears S.38°W., 48 lks. dist. scribed T22S R6W S21 CS BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & C Putnam, crew - Aug-Sept. 1961 - C.S. File 49/143-71

Found - Irving's rock with X on top and 3 notches on N., S., E. and W. faces. 1" Pipe with elbow driven alongside.
Fir tree, now 22", N.21°W. (instead of N.40°W.) 27.1 ft. Tree badly burned and face rotted away.
Fir stump, 22", N.88°E., 32.3 ft. (instead of N.85°E. 38.3 ft.) Cut open scar and found good scribing "R6".
Fir stump 30", S.12°E., (Instead of S.15°E.) 31.7 ft. shows good scar.
No trace of SW BT.

Did Not Set Brass Cap.

New BTs -12" D.Fir S.27°E., 23.5 ft. mkd. T22S R6W S22 CSBT
14" D.Fir N.9°W., 34.3 ft. mkd. T22S R6W S16 CS BT
15" D.Fir N.11°E., 53.3 ft. mkd. T22S R6W S15 CSBT
No trees near in SW.

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #517, surveyed Aug/Sept. 1963 (DCSO records Vol. 32 Page(s) 13450-51)

The Sec. cor., perpetuated and recorded by Irving, 1928, monumented with a sandstone, 14 x 12 x 9 ins., firmly set, 8" in the ground, mkd. with 3 grooves on the N., S., E., and W. faces, from which the remains of the original bearing tree:

A sawed Fir stump 24" dia., bears S.40°E., 111 lks. dist., mkd. T S R on open and burned blaze. (Rec. bearing S.45°E.)

from which bearing trees by Irving:

A sawed Fir stump 22" dia., bears N.85°E., 51 lks. dist., mkd. S15 T22S R6W on opened blaze.

A sawed Fir stump 30" dia., bears S.14 3/4°E., 48 lks. dist. mkd. with a healed blaze.

A broken Fir stump 24" dia., bears N.22 1/2°W., 42 lks. dist. mkd. with illegible scribe marks on splintered face.

and bearing trees by Godfrey:

A Fir 15" dia., bears N.9 3/4°E., 82 lks. dist. mkd. T22S R6W S15 BT on partially healed double blaze.

A Fir 12" dia., bears S.30°E., 33 1/2 lks. dist. mkd. with healed double blaze.

A Fir 13" dia., bears N.8 3/4°W., 53 1/2 lks. dist. mkd. with healed double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22	S R 6 W
S 16	S 15
S 21	S 22
1963	

from which a new bearing tree

A Fir 5" dia., bears S.48 1/4°W., 19 1/2 lks. dist. mkd. T22S R6W S21 BT.

Deposit mkd. stone alongside the iron post.

Found OK by D. Edwards, Mar. 2001 - M136-72

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2875, surveyed Aug. 2017/Feb. 2019- (DCSO records Vol. 59 Page 23644)

The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2 1/2" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd.

from which the remaining bearing tree mkd. by Godfrey, in 1961, filed as CS 49/143-71

Continued next page

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A fir, 29" dia., bears S.30°E., 22.1 ft., with a healed blaze.
and a bearing tree mkd. by Beck in 1963
A fir, 22" dia., bears S.48¼°W., 12.9 ft., with a healed blaze.
and new bearing trees
A fir, 18" dia., bears N.17¾°E., 18.5 ft., mkd. T22S R6W S15 BT.
A fir, 20" dia., bears S.86¾°E., 20.4 ft., mkd. T22S R6W S22 BT.
A fir, 9" dia., bears N. 59° W., 16.1 ft., mkd. X BT.
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.