

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1445)

-----  
(Going North on true line bet. secs. 15 and 16)  
At 38.68 chs.

Set witness cor. ¼ sec. post, from which  
An Alder 30" dia., bears N.75°W., 28 lks. dist.  
An Ash 14" dia., bears N.63°E., 38 lks. dist.

(Traversed creek, regained line on opposite bank and  
At 40.95 chs.

Set witness ¼ sec. post, from which  
A W.Oak 12" dia., bears N.85°W., 38 lks. dist.  
A W.Oak 10" dia., bears N.20°E., 9 lks. dist.

Ben B. Irving, Deputy County Surveyor - Wit: R.L. Irving;  
Jess Widdy - April 1928 - C.S. File 22/25

-----  
True corner falls in Elk Creek.  
Set boulder 6" x 8" x 12" mkd. with X and ½" x 24" pipe  
driven alongside for witness corner, from which scribed  
18" Fir S.24°45'E., 60 lks. dist. W.C. ¼ S15 CS BT.  
36" Fir S.78°15'W., 216 lks. W.C. ¼ S16 CS BT.  
This witness corner is 156 lks., S.0°22'E. of true corner and  
on the West line of Sec. 15.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V.  
Tracy & C. Putnam, crew - Aug/Sept 1961 - C.S. File 49/143-74

-----  
Found - 36" Fir stump, S.78¼°W., 142.6 ft. Stump badly  
burned but found fragments of scribing "SC" on  
burned face.

Burned remnants of Fir stump, S.24 3/4°E., 39.6 ft.  
These two trees were mkd. by Irving in 1928.

No trace of Rock or Pipe set by Irving. Wit. cor. as  
set by Irving falls in center of logging road.

Set Wit. Cor. farther South, out of logging road, Brass cap  
mkd.

County Surveyors Office

T 22 S R 6 W

W.C. ¼ S16|S15

N. 131.5 ft. to corner

1961

New BTs -13" D.Fir S.37½°W., 7.0 ft. mkd. WC ¼ S16 CS BT.

8" D.Fir S.18½°E., 18.2 ft. mkd. WC ¼ S15 CS BT.

True corner falls in Elk Creek, 131.5 ft. North of Witness  
Corner.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #517, surveyed Aug/Sept. 1963 (DCSO records Vol. 32 Page(s) 13452-53)

-----  
(Going N.0°20'W., bet. secs. 15 and 16)

(At 37.86 chs.)

The witness cor. of the ¼ sec. cor. of secs. 15 and 16, established and recorded by Godfrey in 1961, monumented with an iron post, 1½" dia., protruding 14" above the ground, with brass cap mkd. County Surveyors Office

¼ S 16 | S 15

W. C. N.

131.5 ft. to cor.

1961

from which bearing trees by Godfrey

A Fir 8" dia., bears S.18¼°E., 27½ lks. dist. mkd. WC ¼ S15 CS BT on double blaze.

A Fir 13" dia., bears S.37¼°W., 10½ lks. dist. mkd. with a partially healed double blaze.

This witness corner was established by the County when the witness corner point established in 1928 by Irving, was obliterated by a logging road.

(At 38.29 chs.)

The witness cor. of the ¼ sec. cor. of secs. 15 and 16, established and recorded by Irving in 1928, determined from the remains of Irving's 1928 BTs

A stump hole bears S.29 ¾°E., 60 lks. dist.

A sawed Fir stump 36" dia., bears S.78¼°W., 216 lks. dist. mkd. S C on burned face.

This point falls in a dirt road, 20 lks. wide, bears N.65°W., and S.65°E.

(At 39.85 chs.)

True point for the ¼ sec.cor. of secs. 15 and 16, determined at record bearing and distance for the County's 1928 witness corner. The true point falls in Elk Creek, 155 lks. wide, course N.65°W., where it is impracticle to establish a permanent monument.

Found OK by D. Edwards, Mar. 2001 - M136-72