

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 9, 10, 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1445)

Set post cor. of secs. 9, 10, 15 and 16.
Deposited stone 10 x 12, raised mound with trench as per instructions.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy C. Putnam, crew - Oct. 27, 1961 - C.S. File 49/143-92

Corner Report Only
Found - 5/8" reinforcing rod in fence cor. Fences E., W., and S.
Original notes call for rock 10" x 12". No bearing trees set by Gov't surveyor. Plat of Sunnydale Orchards" shows circle but does not mention what monument was set.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #517, surveyed Aug/Sept. 1963 (DCSO records Vol. 32 Page(s) 13453-54)

The Sec. cor., monumented with an old wooden post, 4" sq., 3 ft. long, lying in a mound of stone, 3 ft. base, 1½ ft. high, at intersection of old fence lines extending S. and W.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 22 S R 6 W
S 9 | S 10
S 16 | S 15
1963

from which
A Peach tree 7" dia., bears N.43 3/4°E., 35 lks. dist., mkd. T22S R6W S10 BT.
An Ash 13" dia., bears S.84½°E., 167 lks. dist. mkd. T22S R6W S15 BT.
A Cedar 25" dia., bears S.75½°W., 250 lks. dist. mkd. T22S R6W S16 BT.
An Apple 9" dia., bears N.59¼°W., 11 lks. dist. mkd. T22S R6W S9 BT.

Found OK by W. Eimstad, June 2002 - M140-58