

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1446)

Set post cor. of secs. 3, 4, 9, & 10, from which
A Fir, 50" dia., bears N.70°E., 199 lks.
A fir, 36" dia., bears N.73°W., 45 lks.
A Fir, 30" dia., bears S.48°E., 148 lks.
A Laurel, 5" dia., bears S.45°W., 22 lks.

Survey by George Scroggin - For: Plat of Sunnydale Orchards, Aug. 6, 1914 - Plat Vol. 5 Page 20 A&B

Iron rod.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - 1961 and 1962 - C.S. File 49/143-2 and C.S. File 49/89-40

Corner not found.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 10/10/2001 - C.S. File 66/29-17

Found - 1/2" I.D. iron pipe 4" below ground (1914)
Orig. BTs looked for no positive evidence found:
36" now root hole bears N.73°W., 29.7 ft. (OBT?)
50" now large badly rotted burnt D.Fir stump, no scribing found, bears N.67½°E., 118 ft. (Rec. N.70°E., 131.3 ft.) (OBT?)
50" now large 3½ ft. high rotted D.Fir stump no scribing found, bears N.74°E., 118 ft. (Rec. N.70°E., 131.3 ft.) (OBT?)
30" now large badly rotted burnt stump, no scribing found, bears S.42½°E., 99.4 ft. (Rec. S.48°E., 97.7 ft.) (OBT?)

Set - To protect position of found iron pipe we set a 5/8"x32" long iron rod with a DCSO alum. cap stamped "2001" along south edge of found IP, protrudes 8" above ground.
5" dia., D.Fir double blazed & scribed "X CS BT" bears N.82°E., 8.4 ft.
9" dia., W.Oak double blazed & scribed "X CS BT" bears N.22°W., 17.2 ft.
10" dia., Maple double blazed & scribed "X CS BT" bears S.59°W., 18.4 ft.