

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1447)

Set ¼ sec. post, from which
A Maple 24" dia., bears S.75°E., 97 lks. dist.
A Fir 24" dia., bears S.83°W., 82 lks. dist.

Survey by George Scroggin - For: The Plat of Sunnydale Orchards, Aug. 1914 - Plat Vol. 5 Page 20 A&B

I.P. at ¼ corner.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - Sept. 1961 - C.S. File 49/143-87

Found - 3/4" Iron pipe at corner.
Old Fir stump, now 48", S.83°W., 54.1 ft., shows good scar. Did not open.
Shell of old Maple S.75°E., 64.0 ft., shows old scar but center of tree all burned away.

Alongside 3/4" I. Pipe:
Set Brass cap at cor. mkd: County Surveyors Office
T 22 S R 6 W
¼ S4 | S3
1961

New BTs -4" D.Fir N.77½°W., 35.2 ft. mkd. ¼ S4 CS BT.
6" B.Oak N.23°E., 7.9 ft. mkd. ¼ S3 CS BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 8/16/2001 - C.S. File 66/21-35

Found - 1914 3/4" I.D. iron pipe protrudes 4" out of ground.
1961 DCSO brass cap iron pipe protrudes 10" out of ground along Westerly edge of 3/4" IP.
24" now 48" dia., 6 ft. high rotted and burnt D.Fir stump previously opened with evidence of old blaze illegible reverse scribing & chaining notch visible, bears S.85°W., 54.1 ft. (Rec. S.83°W., 54.1 ft.) (OBT)

Orig. SE Maple not found.
6" now 13" dia., B.Oak with a fully healed blaze, bears N.23°E., 7.9 ft. (1961)
4" now 14" dia., 6" high D.Fir stump no blaze visible bears N.77½°W., 35.2 ft. (1961)

Compass decl. 17¾°E.
New - 20" dia., Maple behind a leaning 10" B.Oak double blazed & scribed "¼ S4 CS BT" bears N.40°W., 22.2 ft.
continued next page

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

9" dia., D.Fir double blazed & scribed "¼ S4 CS BT"
bears N.83°W., 27.6 ft.
25" dia., D.Fir double blazed & scribed "¼ S3 CS BT"
bears S.30½°E., 15.6 ft.

Fd. BC & 4 BTs by Kent Inman - 5/2010 - M160-72A&B