

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664 dated May 23, 1896 (DCSO records Vol 4 Pg 1477)

-----  
Set a Fir post, 3 ft. long. 4" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S on N. face; from which

A Fir 20" dia., bears N.10°W., 9 lks. dist. mkd. 1/4 S BT.

A Fir 12" dia., bears S.82°E., 22 lks. dist. mkd. 1/4 S BT

This cor is on the southerly slope of ridge, 25 ft above ravine

-----  
Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - Aug. 1961 - C.S. File 49/143-50

-----  
Found - Fir tree, now 32", N.10°W., 5.9 ft. Has been opened previously, good scribing visible "1/4S".

1/2" Pipe at corner.

Fir tree, now 20", S.82°E., 14.5 ft. Tree uprooted down & dead, shows good scar. Did not chop open.

Set Brass cap at cor. mkd: County Surveyors Office

T 22 S R 6 W

1/4 S 27

S 34

1961

Set BC alongside iron pipe.

New BTs -14" D.Fir S.42°E., 93.8 ft. mkd. 1/4 S34 CS BT.

15" D.Fir N.60°W., 35.3 ft. mkd. 1/4 S27 CS BT.

-----  
Fd. OK, June 1992, J. Branch, M 115-23

-----  
BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2500, Surveyed July/Aug. 2010 - (DCSO records Vol. 57 Page(s) 22809 & Survey plat 2012-1)

-----  
The 1/4 sec. cor. of secs. 27 and 34. perpetuated by Godfrey, in 1961, monumented with an iron post, 1 1/4" dia., firmly set, projecting 18" above ground (alongside of which is an iron pipe, 1/2" dia., firmly set, projecting 9" above ground, wired to the cor.), with a brass cap (properly) mkd.

from which the remains of the original bearing trees

A roothole bears S.82°E., 4.5 ft., alongside of which is an uprooted, decayed fir, size indeterminate, with no marks visible.

A fir, 38" dia., bears N.10°W., 5.9 ft with a healed blaze and bearing trees mkd by Godfrey

A fir, 23" dia., bears S.40 1/4°E., 93.7 ft., with a healed double blaze.

A fir, 33" dia., bears N.55 1/2°W., 35.1 ft., with a healed double blaze.