TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1444)

Set ¼ sec. post, from which
A Laurel 8" dia., bears N.45°W., 14 lks. dist.
An Alder 6" dia., bears S.54°E., 8 lks. dist.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #517, surveyed Aug/Sept. 1963 (DCSO records Vol. 32 Page(s) 13451)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 23" in the ground, with brass cap mkd:

¼ S 15 / S 22
T 22 S R 6 W
1963

from which
A Fir 23" dia., bears N.7½°E., 70 lks. dist. mkd. ¼ S15 BT.
A Fir 9" dia., bears S.32½°W., 26½ lks. dist. mkd. ¼ S22 BT.

Stephen Stys - Wit: Patrick Coy & Jack Jarrett - 8/7/2024 - C.S. File 65/113-47

Found - A 3¼" brass cap on a 2½" iron pipe (properly) mkd.
A 32" Fir, with a healed face and tag bears N.7°30'E., 46.2' (Per REC)
A 9" Fir stump, with no visible marks bears S.32°30'W., 17.5' (Per record)
New BTs- A 6" Doug fir, faced & scribed "S¼ S15 BT" with X-chop and tag bears N.58°E., 8.7' to a spike at side center.
A 14" Doug fir, faced & scribed "N¼ S22 BT" with X-chop and tag bears S.2°E., 5.7' to a spike at side center.
A 12" Madrone, faced & scribed "S¼ S15 BT" with X-chop and tag bears N.87°W., 8.2' to a spike at side center.
Note - Compass decl. 14½°E.