

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1441)</p> <p>-----</p> <p>Set ¼ sec. post, from which</p> <p> A Fir 10" dia., bears S.75°W., 17 lks. dist.</p> <p> A Fir 15" dia., bears N.75°E., 21 lks. dist.</p>
<p>Wilford N. Haines - Dec. 1958 - M 14-23</p> <p>-----</p> <p>Found - 10" Fir S.75°W., 17 lks., now about 18".</p> <p>Set Lot marker, 1" x 1" x 36" T Iron with brass cap inscribed Survey Point-Wilford N. Haines #239.</p> <p>New BTs -10" Fir S.40°W., 13.0 ft.</p> <p> 36" Fir S.52°E., 9.6 ft.</p>
<p>William Eimstad - For: Cone Lumber - Feb. 1975 - M 55-48</p> <p>-----</p> <p>Found - Haines T Iron at corner.</p> <p> 20" Fir S.74°W., 11.2 ft. Orig. BT.</p> <p> 40" Fir S.55°E., 9.4 ft., bark scribed faces.</p> <p> 14" Fir S.43°W., 13.1 ft., bark scribed faces.</p> <p>Set 2" Iron pipe with brass cap mkd. "T22S R6W ¼ S22 S23 1975 RPLS 377" and place T iron in hole to South.</p> <p>Rescribe-40" Fir S.55°E., 9.4 ft. "¼ S23 BT"</p>
<p>BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1702, Surveyed July/Aug. 1993 - (DCSO records Vol. 51 Page(s) 19440-41)</p> <p>-----</p> <p>The original ¼ sec. cor., perpetuated by Haines in 1958, and further perpetuated and recorded by Eimstad in 1975, monumented with an iron post, 2" dia., firmly set, projecting 2" above the ground, with 1975 brass cap attached, from which the remains of an original bearing tree:</p> <p> A sawed Fir stump 20" dia., bears S.74°W., 17 lks. dist., with a healed blaze.</p> <p>and the remains of bearing trees mkd. by Haines:</p> <p> A Fir 48" dia., bears S.55°E., 15 lks. dist., with scribe marks ¼ visible on the bark and healed blaze.</p> <p> A sawed Fir stump 18" dia., bears S.43°W., 19 3/4 lks. dist., no marks remaining.</p> <p>and a new bearing tree:</p> <p> A Fir 6" dia., bears S.22°W., 20 lks. dist., mkd. ¼ S22 BT</p> <p>The corner is on a NW. slope at the easterly edge of a clearcut logging area.</p>
<p>continued next page</p>

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2500, Surveyed July/Aug. 2010 - (DCSO records Vol. 57 Page(s) 22809 & Survey plat 2012-1)

The ¼ sec. cor. of secs. 22 & 23, monumented with an iron post. 2" dia., firmly set, projecting 1" above ground, with a brass cap (properly) mkd.

from which the remains of an original bearing tree

A sawed fir stump, 39" dia., bears S.74°W., 11.2 ft. with a healed blaze.

and the remains of bearing trees mkd. by Haines in 1958

A fir, 54" dia., bears S.55°E., 9,9 ft., with fragmentary scribe marks visible on bark blaze and a healed blaze.

A sawed fir stump, 18" dia., bears S.43°W., 13.0 ft., with no marks visible.

and a bearing tree mkd. by Bedell

A fir, 12" dia., bears S.22°W., 13.2 ft., with a healed blaze.