

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1442)

Set ¼ sec. post, from which
A Dogwood 5" dia., bears N.80°W., 22 lks. dist.
A Hemlock 24" dia., bears N.30°E., 29 lks. dist.

Ben B. Irving, DCS - Wit: W.S. Crear; Geo Montgomery - Jan. 16, 1928 - C.S. File 22/25

Replaced from
Original Hemlock BT, now 40" bearing proper scribe marks.
Orig. field notes called for 24" Hemlock N.30°E., 29 lks., actually found to be N.30°W. Dist. checks OK.
Stool of Dogwood in position of old Dogwood BT. Orig. field notes call for 5" Dogwood N.80°W., 22 lks., actually found to be S.76°E. Distance checks OK.
Set 6" x 6" x 24" sandstone 12" in ground chisled X-¼ for corner with a 4" x 36" Yew wood post alongside scribed ¼ S.14 S.15 C.S., from which
A 30" Fir bears S.69°35'E., 44 lks. dist. scribed ¼ S14 CS BT.
A 16" Fir bears S.2°15'E., 35 lks. dist. scribed ¼ S14 CS BT.

Wilford N. Haines - Dec. 1958 - M 14-23

Found rock and stake.
Set Lot marker 1" x 1" x 36" T Iron with brass cap inscribed "Survey Point-Wilford N. Haines #239"

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #517, surveyed Aug/Sept. 1963 (DCSO records Vol. 32 Page(s) 13446-47)

The ¼ sec.cor., perpetuated and recorded by Irving in 1928, from the original bearing trees, which are no longer in existence, monumented with a sandstone, 14 x 8 x 6 ins., mkd. ¼ on E. face, firmly set 8" in the ground. In 1958, Wilford Haines set a 1" T Iron 36" long 24" in the ground alongside sandstone.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼
S 15 S 14
T 22 S R 6 W
1963

(Cont. Next Page)

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which new bearing trees
A Hemlock 10" dia., bears S.56°E., 24 lks. dist. mkd. ¼
S14 BT.
A Hemlock 10" dia., bears S.30°W., 44½ lks. dist. mkd. ¼
S15 BT.
Reset the T iron and deposit stone alongside iron post.

Found OK by Harvey Christensen; March 1996 - M123-49