

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1443)</p> <p>-----</p> <p>Set post cor. of secs. 2, 3, 10 and 11, from which An Ash 12" dia., bears S.23°E., 99 lks. dist. An Alder 20" dia., bears S.8°W., 302 lks. dist. An Alder 15" dia., bears N.72°E., 176 lks. dist. Raised mound with trench as per instructions.</p>
<p>George Scroggin - Survey for Plat of Sunnysdale Orchards, Aug. 6, 1914 - Vol. 5 Page 20 A &amp; B</p> <p>-----</p> <p>Iron pipe.</p>
<p>Wilford N. Haines - 1955 - C.S. File 42/75</p> <p>-----</p> <p>Found no trace of iron pipe for corner. Found Ash that looked like BT. Set 36" Angle iron with brass cap inscribed "Survey Point-Wilford Haines No. 239", N.23°W., 99 lks. from the Ash tree. Nailed a brass survey point on 16" Ash which bears S.05°08'E., 26.8 ft.</p>
<p>Fd. OK, August 1981, R. Dean, M 88-65</p>
<p>Survey by James A. Branch - For: U.S. National Bank of Oregon March 23, 1990 - C.S. File 63/104-8 and M 109-74 A&amp;B</p> <p>-----</p> <p>Found - T Iron set by Haines. Brass cap on top of T Iron is missing. 30" (16" 1955) Ash BT bearing S.5°08'E., 26.8 ft. lying on the ground. New BTs -8" Ash scribed "SE S3 BT" bears N.8°44'W., 175.6 ft. 13" W.Oak scribed "SW S1 BT" bears N.58°09'E., 132.5 ft. 27" W.Oak scribed "NW S11 BT" bears S.66°09'E., 100.4 ft. 26" Ash scribed "NE S10 BT" bears S.29°53'W., 79.9 ft.</p>
<p>Found OK by L. Roberts, June 2000 - M135-8</p>
<p>DCSO-GIS Corner visitation - 9/6/2001 - Typed: 1/19/2011 - C.S. File 67/33-1</p> <p>-----</p> <p>Monument - IP</p>