

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35, T21-6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 692-93)

-
- Set post cor. of secs. 2, 3, 34 and 35; from which
- A Fir 12" dia., bears S.70°W., 34 lks. dist.
 - A Fir 60" dia., bears S.57°E., 64 lks. dist.
 - A B.Oak 8" dia., bears N.53°E., 67 lks. dist.
 - A B.Oak 8" dia., bears N.19°W., 38 lks. dist.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #514, dated Aug. 27, 1884 (DCSO records Vol. 2 Page(s) 700-01)

-
- At the Sec. cor., found the post gone and only one bearing tree standing. Reestablished the same by setting post, 6" dia., 4 ft. long, with marked stone, 12" in ground, mkd. T21S S35 on NE.; R6W S2 on SE.; T22S S3 on SW.; S34 on NW.; face, with two notches on E. and 4 on W. edges; from which
- Fir 24" dia., bears S.70°W., 34 lks. dist., mkd. T22S R6W S3 BT.
 - Oak 14" dia., bears N.14°W., 61 lks. dist. mkd. T21S R6W S34 BT.
 - Fir 14" dia., bears S.2°E., 56 lks. dist., mkd. T22S R6W S2 BT.
 - Fir 6" dia., bears N.58°E., 98 lks. dist., mkd. T21S R6W S35 BT.

Wilford N. Haines - For: Harold Woolley - Jan. 21, 1958
M 8-30

-
- Found - Orig. BT to SW., stump.
- Scribed -18" Fir N.31°W., 36.8 ft.
 - 30" Fir S.81°W., 21.3 ft.
 - 8" Fir N.83°E., 48.3 ft.
 - 40" Fir S.03°E., 37.0 ft.
- Set 1" x 1" x 36" Iron T Iron rod with brass cap.

Survey by Les Roberts - For: Seneca Timber Co. - Feb. 10, 1994 - M 118-39

-
- Found - Haines T Iron set in survey M 8-30
- 22" Fir stump S.72°W., 22.5 ft., scribe visible.
 - 40" Fir stump S.02°E., 37.0 ft., bark scribe.
 - 16" Fir stump N.83°E., 48.5 ft., scar visible.
 - 20" Fir stump N.30°W., 36.8 ft., scar visible.
 - 38" Fir stump S.83°W., 21.5 ft., bark scribe.
 - 40" Fir stump S.02°E., 37.0 ft., bark scribe.

(Cont. Next Page)

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35, T21-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs -8" Oak S.39°W., 47.3 ft., scribed, washer, painted red.
12" Oak S.11°E., 66.4 ft., scribed, washer, painted red.