

PRIMARY CORNER DESCRIPTION Center 1/4 Corner for Section 23

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

Wilford N. Haines - Dec. 1958 - M 14-23

Set Lot marker, 1" x 1" x 36" T Iron with brass cap inscribed
"Survey Point-Haines #239"
Scribed -15" Fir N.78°E., 5.0 ft.
14" Fir S.53°W., 20.5 ft.

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under
Group #1702, Surveyed July/Aug. 1993 - (DCSO records Vol. 51
Page(s) 19438)

The center 1/4 cor., established and recorded by Haines in
1958, and is accepted as the corner; monumented with a T
shaped iron rod, 1" dia., firmly set, projecting 12" above
the ground, with a brass disk attached to the top, mkd.
WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which
bearing trees mkd. by Haines:

A Fir 22" dia., bears N.78°E., 7½ lks. dist., with scribe
marks C ¼ visible on the bark.

A Fir 24" dia., bears S.53°W., 31 lks. dist.; with scribe
marks C ¼ S BT visible on the bark.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 16" in
the ground, directly over the iron rod, with brass cap mkd:

T22S R6W
C 1/4 S 23
1993

Deposit white "DEEP-1" magnetic marker at base of stainless
steel post.

The corner is located in a wire fence line, extending N. and
S., and 10 lks. N. of a wire fence line, extending W.