

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1441)

-----  
Set ¼ sec. post, from which  
A Fir 48" dia., bears N.63°W., 149 lks. dist.  
A Fir 12" dia., bears S.70°W., 304 lks. dist.

-----  
Wilford N. Haines - Dec. 1958 - M 14-23

-----  
Set Lot marker, 1" x 1" x 36" T iron with brass cap inscribed "Survey Point-Wilford N. Haines #239" (Set midway)

-----  
BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1702, Surveyed July/Aug. 1993 - (DCSO records Vol. 51 Page(s) 19434)

-----  
The ¼ sec. cor., reestablished and recorded by Haines in 1958, and is accepted as the corner; monumented with a T shaped iron rod, 1" dia., firmly set, projecting 3" above the ground.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 22" in the ground, directly over the iron rod with brass cap mkd:

T22S R6W

1/4  $\frac{S\ 14}{S\ 23}$

1993

from which new bearing trees:

A Fir 6" dia., bears S.43°E., 5 lks. dist. mkd. ¼ S23 BT

A Fir 10" dia., bears N.22°W., 55 lks. dist. mkd. ¼ S14 BT