

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 540540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Section 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by James A. Branch, LS #1138 - For: U.S. National Bank of Oregon - March 1990 - C.S. File 63/104-11 and M 109-74 A&B

-----  
Corner was set at the straight line intersection point between the North and South ¼ sec. corners and the East and West ¼ sec. corners. Existing N-S fence is West, 18.5 ft. more or less from the corner.

Set 5/8" x 30" rebar with yellow plastic cap mkd. "Branch Eng LS1138".

Blazed and scribed bearing trees as follows:

- 15" D.Fir scribed "C¼ S11 BT" bears N.12°30'W., 44.9 ft.
- 5" D.Fir scribed "C¼ S11 BT" bears N.66°30'E., 64.4 ft.
- 20" D.Fir scribed "C¼ S11 BT" bears S.19°15'E., 29.7 ft.
- 17" D.Fir scribed "C¼ S11 BT" bears S.51°30'W., 17.8 ft.

Found OK by L. Roberts, June 2000 - M135-8