

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 2; & 35, T21-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 692)

-----  
Set ¼ sec. post, from which  
    An Ash 15" dia., bears N.87°E., 536 lks. dist.  
    A B.Oak 30" dia., bears S.20°E., 380 lks. dist.

Wilford N. Haines - For: Harold Woolley - Jan. 21, 1958  
M 8-30

-----  
Scribed -18" Fir S.45°15'E., 80.1 ft.  
          18" W.Oak N.82°30'E., 182.5 ft.  
Set 1" x 1" x 36" Iron T-Iron rod with brass cap.

Fd. OK, Aug. 1961, DCSO, C.S. File 49/143-40

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 8/14/2001 - C.S. File 66/21-34

-----  
Found - 1958 Haines "T" iron protrudes 12" out of ground.  
          Top bent 10" SE.  
          18" now 22" dia., 4 ft. high D.Fir stump with fully  
          healed blaze, bears S.45¼°E., 80.1 ft. (1958)  
          18" now 22" dia., 3 ft. high W.Oak stump with fully  
          healed blaze bears N.82½°E., 182.5 ft. (1958)  
New - 14" dia., W.Oak double blazed & scribed "¼ S35 CS  
          BT" bears N.61°E., 360.6 ft.  
          19" dia., W.Oak double blazed & scribed "¼ S2 CS BT"  
          bears S.33°W., 157.6 ft.  
          Compass decl. 17¾°E.  
          At plumb position of found "T" iron we set a 2 3/8"  
          dia., brass cap on a 1 3/8" O.D. by 32" long iron  
          pipe. Protrudes 4" out of ground. "T" iron set  
          along North edge of BC/IP protrudes 1" out of  
          ground. MKD: DOUGLAS COUNTY SURVEYOR

T21S  
    S 35 R  
    S 2 6  
T22S W  
2001

Set metal witness post and sign 1 ft. East of BC/IP.  
Corner is approx. East 300 ft. from old cemetery.

Fd. OK by H. Christensen, Oct. 2004 -M145-69