

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 548100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 2 only, T23-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1427)

Set Standard $\frac{1}{4}$ sec. post, from which
A Fir 12" dia., bears S.45°E., 20 lks. dist.
A Fir 36" dia., bears S.60°W., 17 lks. dist.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12625)

Point for the standard $\frac{1}{4}$ sec. cor. of sec. 2, at proportionate distance; there is no remaining evidence of the original corner.
Set and iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap mkd:

$\frac{1}{4}$ S 2
S C
1943

from which
A Fir 24" dia., bears S.18°E., 87 lks. dist. mkd. $\frac{1}{4}$ S2 SC BT.
A Fir 18" dia., bears S.57°W., 57 lks. dist. mkd. $\frac{1}{4}$ S2 SC BT.

Fd. OK, June 1992, J. Branch, M 115-26

Fd. & used on BLM corrective and dependent resurvey by Wayne L. Rogers, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1803 surveyed May/Nov.. 1996 - (DCSO records Vol. 52 Page(s) 19958)