

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCS0 records Vol. 4 Page(s) 1434)

-----  
Set post cor. of secs. 25, 26, 35 and 36, from which  
A Fir 8" dia., bears S.25°W., 14 lks. dist.  
A Fir 12" dia., bears S.35°E., 44 lks. dist.  
A Fir 8" dia., bears N.44°E., 50 lks. dist.  
A Fir 6" dia., bears N.6°W., 13 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; A. Bilow - April 13, 1959 - C.S. File 49/143-33

-----  
Found - Three original BTs, all check bearings and distances:  
Orig. SW. BT, now 40" rotted stump, shows good scribing on old face "35 22".  
Orig. NW BT, now short stub, shows good scribing "BT".  
Orig. NE BT shows good scribing on small section of stub.  
No trace of original SE BT found.

Set Brass cap at cor. mkd: County Surveyors Office  
T 22 S R 6 W  
S 26 | S 25  
S 35 | S 36  
1959

North-South fence 50.0 ft. more or less, West.  
New BTs -8" R.Fir bears N.55°W., 82.7 ft. scribed S26 T22S R6W CS BT.  
13" R.Fir bears N.26°E., 67.3 ft. scribed S25 T22S R6W CS BT.  
9" W.Fir bears N.63½°E., 124.6 ft. scribed S25 T22S R6W CS BT.  
No suitable trees to South.

Fd. OK, Aug. 1990, M 110-47  
Fd. OK, June 1992, M 115-26  
Fd. OK, Aug. 1992, J. Branch, M 115-52  
Fd. OK, Aug. 1994, K. Hoffine, M 120-79  
Fd. OK, Oct. 2007, R Betz, M154-40 (replaces M116-29)

David Edwards - Crew: Brant Miller & Eric Sprinkle - 7/22/2024 - C.S. File 65/113-43

-----  
Found - 1959 DCS0 brass capped iron pipe.  
All previous BTs are gone.  
New - An 11" dia., Fir scribed "T22S R6W S36 BT" bears S.79°E., 9.44 ft. Continued next page

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

A 9" dia., Fir scribed "T22S R6W S35 BT" bears  
S.28°W., 15.3 ft.  
5.5 ft steel posts are set 2 ft South and 2 ft North  
on line.

Note - Compass decl. 15°E.